



Representative

Catalog Number: Product ID: UPC Number: Status:

ATD266336CB 7TAA267140R0004 78378617624 Active

Autoset Clevis Bracket Automatic Tension Deadend for Wire Range: 266 18/1, 336 18/1 AS-CR, 266, 336 AAAC, 266, 336 AAAC, Color Code Green

UNSPSC	39121431 Cable gland connector
IGCC	4601 Cable gland connector
Brand Name	Blackburn
Туре	Dead-End with Clevis Bracket
Special Features	Versatile for Dead-Ending ACSR, AAC and AAAC Conductors. Breaking Strength exceeds 95 per- cent of Conductors Rated Strength, up to maximum of 10,000 pounds. Galvanized Steel Clevis Pin an Stainless Steel Cotter Pin are included enable the bail to be used with standard deadend supsension insulators. Grab and go - slots are provided for use with Standard pulling hooks.
Application	Cable Dead-End
Size	Length 19-3/16 inches
Conductor Range	266 18/1, 336 18/1 ASCR, 266, 336 AAAC, 266, 336 AAC,
Number Of Conductors	1
Material	Aluminum Body, Stainless Steel Bail
Finish	Bare
Voltage Rating	35kV
Amperage Rating	Equal to Conductor
Insulation	None
Mounting	Yes
Connection	Tension
Environmental Conditions	All Seasons / Conditions

Packaging

Outer Quantity	3
Outer Dimensions (inches)	23.5x9.2x4.2
Weight Uom	2.7 lbs. Each

Documents / Support Tools

Technical Data Sheet CA

Available on Website

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com