



Family

Catalog Number: **ATS20**
Product ID: 7TAA267130R0004
UPC Number: 78378614180
EAN Number: 05415022348460
Status: Active

Autoset Automatic Tension Splice for Wire Range: 2/0 7/1 ASCR, 2/0 AAAC, 2/0 AAC, Aluminum, Color Code 2/0 - Gray

UNSPSC Specifications

UNSPSC	39121449 Wire or cable compression splice
IGCC	4669 Wire or cable compression splice
Brand Name	Blackburn
Type	Autoset Automatic Splice
Special Features	Color-Coded, funnel-shaped end pieces provide instant visual identification of maximum conductor size and swiftly guide conductor into position for insertion. Pilot caps envelop cable strands and guide the conductors into the center of the splice. Die-cast precision-made jaws provide optimum contact area for a greater range of conductor sizes. Compression spring positions the jaw for positive conductor acceptance. Tubular center stop automatically determines proper insertion length of both conductors. High-strength aluminum-alloy tubing covers the connection for superior corrosion protection and long-lasting durability. Color-coded tape enables identification of the minimum conductor size of wide-range connectors - it further eliminates errors and speeds up installation.
Application	Make quick, dependable overhead tension splices and speed up installation time.
Size	Overall Length 16.25 inches
Connection	Tension
Conductor Range	2/0 7/1 ASCR, 2/0 AAAC, 2/0 AAC
Number Of Conductors	2
Material	Aluminum
Finish	Bare
Color	Gray
Voltage Rating	35kV
Insulation	None
Mounting	None
Environmental Conditions	All Seasons / Conditions

Packaging

Inner Quantity	1
Outer Quantity	25
Outer Dimensions (inches)	17x7x7
Weight Uom	6.25 lbs. per 100

Documents / Support Tools

Technical Data Sheet CA	Available on Website
-------------------------	----------------------

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
 www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321

