



Representative



Representative

**Catalog Number:** CSC64  
**Product ID:** 7TAA267190R0022  
**UPC Number:** 78378610070  
**Status:** Active

Aluminum 2 inch Service Entrance Compression Splice with C2BB Cover for Wire Range - End A: 12 ASCR, 6 Str., 4 Sol., Blue, End B: 6 6/1 ASCR, 6 Str., 4 Sol., Blue, Die: 5/8

**UNSPSC Specifications**

UNSPSC	39121449 Wire or cable compression splice
IGCC	4669 Wire or cable compression splice
Brand Name	Blackburn
Type	Service Entrance Connectors
Special Features	Sleeves are made of highly conductive aluminum. Quick identification with color-coded foil caps. Installs with standard compression tools.
Application	Basic, uninsulated Splices for Service Entrances. For Combinations of Aluminum-to-Aluminum or Aluminum-to-Copper Conductors.
Standard	RUS Listed. Passes the Requirements of ANSI C119.4
Size	2 Inch
Connection	Crimp/ Compression
Conductor Range	End A: 12 ASCR, 6 Stranded, 4 Solid, Blue, End B: 6 6/1 ASCR, 6 Stranded, 4 Solid.
Number Of Conductors	2
Material	Aluminum Sleeve, Polyethylene Cover
Insulation	Cover acts as insulation
Mounting	None
Environmental Conditions	All Seasons / Conditions

**Packaging**

Outer Quantity	100
Outer Dimensions (inches)	14x7.5x6.8
Weight Uom	11 lbs. per 100

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
www.tnb.com

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email:techsupport@tnb.com