



Representative



Representative

Catalog Number: CSC68
Product ID: 7TAA267190R0024
UPC Number: 78378610074
Status: Active

Aluminum 2 inch Service Entrance Compression Splice with C2BB Cover for Wire Range - End A: 4 6/1,7/1 ASCR, 3-4 Str., 2 Sol., Orange, End B: 4 6/1,7/1 ASCR, 3-4 Str., 2 Sol., Orange, Die: 5/8

UNSPSC Specifications

UNSPSC	39121449 Wire or cable compression splice
IGCC	4669 Wire or cable compression splice
Brand Name	Blackburn
Type	Service Entrance Connectors
Special Features	Sleeves are made of highly conductive aluminum. Quick identification with color-coded foil caps. Installs with standard compression tools.
Application	Basic, uninsulated Splices for Service Entrances. For Combinations of Aluminum-to-Aluminum or Aluminum-to-Copper Conductors.
Standard	RUS Listed. Passes the Requirements of ANSI C119.4
Size	2 Inch
Connection	Crimp/ Compression
Conductor Range	End A: 4 6/1,7/1 ASCR, 3-4 Stranded, 2 Solid, End B: 4 6/1,7/1 ASCR, 3-4 Stranded, 2 Solid.
Number Of Conductors	2
Material	Aluminum Sleeve, Polyethylene Cover
Insulation	Cover acts as insulation
Mounting	None
Environmental Conditions	All Seasons / Conditions

Packaging

Outer Quantity	100
Outer Dimensions (inches)	14x7.5x6.8
Weight Uom	9.89 lbs. per 100

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
 www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email:techsupport@tnb.com