



Representative

Catalog Number: **DLC23**
Product ID: 7TAA267270R0004
UPC Number: 78378694963
Status: Active

Type DLC - Single U-Bolt Aluminum Fittings for Wire Range Main AWG or kcmil 266.8 - 1/0 Stranded, ACSR Main 4/0 - 1, 2 - 6 AR. 2-3/8 inch wide X 2-7/8 inch long X 4 inch high.

North American Specifications (UNSPSC)

UNSPSC	39121408 Mechanical connectors
IGCC	4541 Mechanical connectors
Brand Name	Blackburn
Type	Deadend Loop Connection
Special Features	Top and Bottom Pressure Pads cast of High-Strength, Heat-Treated, Aluminum-Silicon Alloy. Hardware made of Galvanized Steel Provides Added Strength and Durability.
Application	Dead-End Loop Connections
Connection	Mechanical
Number Of Conductors	2
Material	Aluminum
Finish	Bare
Voltage Rating	35kV
Insulation	No
Conductor Range (Main/Primary)	ACSR 4/0 - #1 or #2-#6 Armored Rod, AWG or KCMIL 266.8 - 1/0 Stranded
Conductor Range (Tap/Secondary)	ACSR 4/0 - #1, AWG or KCMIL 266.8 - 1/0 Stranded
Bolt Size	1/2 inch

Packaging

Outer Quantity	25
Outer Dimensions (inches)	14x7.1x6.7
Weight Uom	90.19 lbs. per 100

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com