



Representative

**Catalog Number:** FBXD12  
**Product ID:** 7TAA014910R0089  
**UPC Number:** 78621010649  
**Status:** Active

FLEXIBLE BRAID 105.6 KCMIL, 12 INLG

- Tin-plated copper braids and ferrules for high conductivity and corrosion resistance.
- Certified C22.2 No. 41 Grounding and Bonding Equipment. Listed UL467 and UL486A for Grounding and Bonding Equipment.
- Flexible copper braids for use in substation and grounding applications.

### UNSPSC Specifications

UNSPSC	39121465 Flexible braid
IGCC	4695 Flexible braid
Brand Name	Blackburn
Type	Flexible Braid
Special Features	Tin-plated copper braids and ferrules for high conductivity and corrosion resistance.
Application	Flexible copper braids for use in substation and grounding applications.

### Packaging

Outer Quantity	1
Outer Dimensions (inches)	12x1.25x.2
Weight Uom	41 lbs. per 100

### Documents / Support Tools

Technical Data Sheet CA	Available on Website
-------------------------	----------------------

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
www.tnb.com

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email:techsupport@tnb.com