



Blackburn®

Copper Connectors
T&B Catalog Number:

UPC Number: L250P
Status: 78378612998
Description: Active

Type L - Copper Tin-Plated Single Conductor, One-Hole Mount for Conductor Range 6 Str.-250 kcmil

Features

Cold forged from pure electrolytic copper with 99 percent conductivity.

General

Style	Type L - Copper Single Conductor, One-Hole Mount
Material	Copper
Plating	Tin-Plated
Wire Range	6 Str.-250 kcmil

Dimension Information

Length (inches)	1 61/64
Width (inches)	15/16
Height (inches)	1 1/16
D (inches)	29/64
E (inches)	13/32
F (inches)	1/8
G (inches)	1 3/32
J (inches)	5/8

Packaging

T&B Inner Pack	10
Package in Units	50
T&B Sold in UOM	Each
T&B Weight Per UOM	17.31 lbs. per 100

Notes

Socket screw.
 UL 486A tested.

Certifications

RoHS Compliance Yes

Certifications



File Nbr:
 E9809

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
 www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email:techsupport@tnb.com

