



Actual

Family

**Catalog Number:** OAPA-250  
**Product ID:** 7TAA007480R0018  
**UPC Number:** 07511413374  
**Status:** Active

Aluminum Solid Pin Terminals Offset Pin Style with Insulating EDPM Rubber Boot, Wire Size 250 kcmil, Overall Length 2.63 Inches (66.80mm), Tin Plated, Die Code 87, Brown

- Tooth design to provide greater holding force. One piece connector design for increased reliability.
- UL Listed with T&B and competitor application tooling.
- Pin designed to have greater cross-sectional area than conductor. EPDM rubber or PVC boot provided to eliminate the need for any taping.
- Termination of aluminum or copper conductors to mechanical lugs.

#### UNSPSC Specifications

UNSPSC	39121405 Cable or wire lug
IGCC	4532 Cable or wire lug
Brand Name	Blackburn
Type	Pin Adapters
Special Features	Pin Adapters
Application	Termination of aluminum or copper conductors to mechanical lugs.
Voltage Rating	600V
Material	Aluminum
Color	Brown

#### Packaging

Outer Quantity	10
Outer Dimensions (inches)	8.1x6.7x7.7
Weight Uom	0.21 lbs. Each

#### Documents / Support Tools

SDS US 1	sds-00041-tb2
Technical Data Sheet CA	Available on Website

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
www.tnb.com

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email:techsupport@tnb.com