

Actual

Family

Catalog Number: OAPA-600
Product ID: 7TAA007480R0022
UPC Number: 07511413383
Status: Active

Aluminum Solid Pin Terminals Offset Pin Style with Insulating EDPM Rubber Boot, Wire Size 600 kcmil, Overall Length 3.67 Inches (93.22mm), Tin Plated, Die Code 115, Yellow

- Tooth design to provide greater holding force. One piece connector design for increased reliability.
- UL Listed with T&B and competitor application tooling.
- Pin designed to have greater cross-sectional area than conductor. EPDM rubber or PVC boot provided to eliminate the need for any taping.
- Termination of aluminum or copper conductors to mechanical lugs.

UNSPSC Specifications

UNSPSC	39121405 Cable or wire lug
IGCC	4532 Cable or wire lug
Brand Name	Blackburn
Type	Pin Adapters
Special Features	Pin Adapters
Application	Termination of aluminum or copper conductors to mechanical lugs.
Voltage Rating	600V
Material	Aluminum
Color	Yellow

Packaging

Outer Quantity	3
Outer Dimensions (inches)	7.5x6.75x4.5
Weight Uom	43.5 lbs. per 100

Documents / Support Tools

SDS US 1	sds-00041-tb2
Technical Data Sheet CA	Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com