



Actual

Catalog Number: **SGAC 500**
Product ID: 7TAA262900R0011
UPC Number: 78378675159
Status: Active

Aluminum Multi-Range Dieless Compression Splices - Minimum Tension, conductor size 4/0 str-500-477 (18/1), decimal range min outside diameter .522, decimal range max outside diameter .814, tool - VC-6, length 5 in

UNSPSC Specifications

UNSPSC	39121449 Wire or cable compression splice
IGCC	4669 Wire or cable compression splice
Brand Name	Blackburn
Type	Aluminum Multi-Range Dieless Compression Splice
Special Features	Dual-rated. Use with Aluminum and Copper conductors. All splices are marked with conductor size for easy identification. Solid center stop ensures proper cable insertion. Connector Bores coated with Oxide Inhibitor and Capped to Prevent Oxidation. Made from Aluminum for high strength and high conductivity.
Size	5 inches long
Connection	Crimp/Compression
Conductor Range	4/0 Stranded - 500 - 477(18/1)
Material	Aluminum
Insulation	Non-Insulated

Packaging

Outer Quantity	25
Outer Dimensions (inches)	8.1x6.3x6.7
Weight Uom	32.5 lbs. per 100

Documents / Support Tools

SDS US 1	sds-00042-tb2
Technical Data Sheet CA	Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com