

## Toughstripe® Floor Marking Signs

Toughstripe B-534 polyester floor signs resist harsh chemicals and are specifically designed to alert workers of potential dangers and enforce protective equipment requirements.

- Exceeds safety standards for clean, dry non-slip surfaces per ANSI A1264.2-2006 and OSHA 1910.22
- 3 mil thickness; Service temperature range of 0°F – 129°F
- Black areas of signs are coated with anti-skid tread
- US Patent No: 8,302,337



104489 17" dia. TS    104495 17" dia. TS    104496 17" dia. TS    104490 17" dia. TS    104492 17" dia. TS    104493 17" dia. TS    104494 17" dia. TS



104509 17" dia. TS    104501 17" dia. TS    104512 17" dia. TS    104513 17" dia. TS    104486 17" dia. TS    104487 17" dia. TS    104507 17" dia. TS



104511 17" dia. TS    104508 17" dia. TS    104488 14" x 18" TS    104491 14" x 18" TS    104497 14" x 18" TS    104498 14" x 18" TS    104499 14" x 18" TS



104500 14" x 18" TS    104502 14" x 18" TS    104503 14" x 18" TS    104504 14" x 18" TS    104505 14" x 18" TS    104506 14" x 18" TS    104510 14" x 18" TS

### Watch Toughstripe® Floor Marking Material in Action

ToughStripe® Floor Marking Tape is test-proven to withstand forklift traffic better than other tape-based floor marking products. That means less tearing. Less lifting. And less time re-applying your floor marking.

Visit [BradyID.com/toughstripe](http://BradyID.com/toughstripe) to view the video.

