

STAINLESS STEEL FLEXIBLE CONDUIT


Coated Flex Conduit 25' Length			NEMA4X		Suitable for damp locations	
Trade Size	Metric Size	Outside Dia.	Inside Dia.	Bend	Wt. 25' Coil (lbs)	Part Number
½"	16	0.840"	0.610"	4-½"	5.50	S40500CTFC
¾"	21	1.050"	0.790"	6"	7.00	S40700CTFC
1"	27	1.315"	1.010"	10"	9.00	S41000CTFC
1-¼"	35	1.660"	1.330"	11"	11.00	S41200CTCC
1-½"	41	1.900"	1.520"	12"	12.00	S41500CTFC



Clear Coated Flex Conduit 25' Length			NEMA4X		Suitable for damp locations	
Trade Size	Metric Size	Outside Dia.	Inside Dia.	Bend	Wt. 25' Coil (lbs)	Part Number
½"	16	0.840"	0.610"	4-½"	5.50	S40500CTCC
¾"	21	1.050"	0.790"	6"	7.00	S40700CTCC
1"	27	1.315"	1.010"	10"	9.00	S41000CTCC
1-½"	41	1.900"	1.520"	12"	12.00	S41500CTCC




Bare Flex Conduit 25' Length			NEMA4X		Suitable for damp locations	
Trade Size	Metric Size	Outside Dia.	Inside Dia.	Bend	Wt. 25' Coil (lbs)	Part Number
½"	16	0.744"	0.610"	4"	4.50	S60500CTFX
¾"	21	0.960"	0.790"	4-½"	5.50	S60700CTFX
1"	27	1.160"	1.010"	6"	7.00	S61000CTFX
1-¼"	35	1.500"	1.330"	7-½"	8.50	S61200CTFX
1-½"	41	1.750"	1.520"	9"	10.00	S61500CTFX
2"	53	2.125"	2.020"	10"	13.00	S62000CTFX




STAINLESS STEEL FLEXIBLE CONNECTORS (Type 316SS)

Flex Connector Male 90° Elbow		<i>NEMA4X</i>	Suitable for damp locations			
Trade Size	Metric Size	Wt. (lbs)	A	B	C	Part Number
½"	16	0.29	1.900"	1.150"	1.380"	S60500FC90
¾"	21	0.50	2.250"	1.400"	1.710"	S60700FC90
1"	27	0.75	2.800"	1.780"	2.140"	S61000FC90
1-¼"	35	1.00	3.290"	2.250"	2.500"	S61200FC90
1-½"	41	1.38	3.750"	2.500"	2.960"	S61500FC90
2"	53	1.55	4.450"	2.830"	4.420"	S62000FC90



Flex Connector Male Straight		NEMA4X Suitable for damp locations			
Trade Size	Metric Size	Wt. (lbs)	A	B	Part Number
½"	16	0.15	1.530"	1.200"	S60500FCS0
¾"	21	0.22	1.675"	1.500"	S60700FCS0
1"	27	0.33	1.800"	1.650"	S61000FCS0
1-¼"	35	0.70	2.000"	2.250"	S61200FCS0
1-½"	41	0.83	2.000"	2.480"	S61500FCS0
2"	53	1.00	2.190"	2.830"	S62000FCS0



*45° Flex Connectors available in ½" and ¾".