



Color-Keyed®

Washers T&B Catalog Number:

60803-TB

UPC Number: 78621060803 Status: Active


Description:

Belleville Spring Washer, 1/2 Inch Bolt Size, Steel with Zinc Chromate

Finish

Application

For tight, secure bus-bar connections.



| | <u> </u> |
|---------------------------------------|--------------------------|
| General | |
| Style | Belleville Spring Washer |
| Material | Steel |
| Finish | Zinc Cromate |
| Stud Size | 1/2 |
| Dimension Information | |
| | |
| C (inches) | .813 |
| D (inches) | .095 |
| Specifications | |
| Recommended Installing Torque In-Lbs. | 175 - 200 |
| Packaging | |
| T&B Order Multiple | 25 |
| T&B Inner Pack | 25 |
| Package in Units | 250 |
| T&B Sold in UOM | Each |
| T&B Weight Per UOM | 2.5 lbs. per 100 |
| | |

When bolting aluminum lugs and connectors to buss bars with steel or brass hardware, the recommended practice to ensure a tight connection is to use a Belleville spring washer on top of a flat washer under the bolt head or nut. For heavy-duty

service where the heat rise is expected to exceed 30 degrees Celcius above ambient, this procedure maintains constant pressure as the connector metals expand and contract with temperature changes.

Certifications

Notes

RoHS Compliance Yes

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125

Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com