

Heavy Duty Narrow Channel



FEATURES

- · One or two lamp cross sections
- · Die formed steel channel for extra strength
- · Snap-on cover, no tools required
- Rotary lock lampholders
- · Channel ends double as joiners
- · Individual or row mounting, surface or suspended
- All metal parts are treated with a five stage phosphate bonding process and finished with a baked white enamel
- UL listed 1598, cUL or CSA. Damp Location standard

ORDERING INFORMATION

MODEL

CH

CH Heavy Duty Narrow Channel

SIZE 2 2' **3** 3'

- 4 4' 8 8'
- 16 16' (Two housings)

NO. OF LAMPS IN CROSS SECTION

- **1** One
- 2 Two

See Product Availability table

LAMP TYPE

- 14 2', T5: 14 Watt
- 17 2', T8: 17 Watt 21 3', T5: 21 Watt
- 24 2', T5H0: 24 Watt
- 25 3', T8: 25 Watt 28 4', T5: 28 Watt
- **32** 4', T8: 32, 30, 28 or 25 Watt
- **39** 3', T5H0: 39 Watt
- **54** 4', T5H0: 54 or 51 Watt

BALLAST

NOTE: See Technical Section for other ballast options.

- E Electronic T8, Instant
- 4E 4-Lamp Electronic T8, Instant Start
- EP Electronic T5 or T8, **Programmed Start**
- **4EP** 4-Lamp Electronic T5HO (N/A 347V) or T8, Programmed Start

VOLTAGE

U 120V-277V

347 347V

OPTIONS

GLR Fast Blow Fuse

EL Emergency Battery Pack

PAF Paint After Fabrication

*Not available in all lamp/ ballast combinations. For more options see pages 96-112.

ACCESSORIES (ORDER SEPARATELY)

CHWG4* 4' Wire Guard


CHR4* 4' Symmetric Reflector (1-Lamp only)

CHRA4* 4' Asymmetric Reflector (1-Lamp only)

S18 18" Stem, 8° Swivel Stem and Canopy SS18 18", 45° Swivel Stem, and Canopy

*2' and 3' also available; replace 4 in catalog number.

For more accessories see pages 99-101.



PRODUCT AVAILABILITY						
SIZE	NO. OF LAMPS IN CROSS SECTION	NO. OF LAMPS IN FIXTURE	LAMP TYPE	WIDTH	LENGTH	HEIGHT
2'	1	1 2	14, 17, 24	3¾6"	24"	1¾16"
2'	2		14, 17, 24	3¾6"	24"	1¾16"
3'	1	1	21, 25, 39	3¾16"	36"	1¾16"
3'	2	2	21, 25, 39	3¾16"	36"	1¾16"
4'	1	1	28, 32, 54	3¾16"	48"	1¾16"
4'	2	2	28, 32, 54	3¾16"	48"	1¾16"
8'	1	2	28, 32, 54	3¾16"	96"	1¾16"
8'	2	4	28, 32, 54	3¾16"	96"	1¾16"
16' (Two Housings)	1 2	4	28, 32, 54	3¾6"	192"	1¾6"
16' (Two Housings)		8	28, 32, 54	3¾6"	192"	1¾6"

