



Powering Business Worldwide

9566TRDS

GFCI Aspire TR 15A 125V 2P3W DS

UPC: 032664665592

Brand Name: Cooper Wiring Devices

Sub Brand: ASPIRE RF

Voltage Rating: 120 Vac

Frequency Rating: 60 Hz

Wattage: 600 W

9566TRDS-K

GFCI Aspire TR 15A 125V 2P3W DS

UPC: 032664716515

Brand Name: Cooper Wiring Devices

Sub Brand: ASPIRE RF

Voltage Rating: 120 Vac

Frequency Rating: 60 Hz

Wattage: 1000 W

9566TRSG

GFCI Aspire TR 15A 125V 2P3W SG

UPC: 032664665608

Brand Name: Cooper Wiring Devices

Sub Brand: ASPIRE RF

Voltage Rating: 120 Vac

Frequency Rating: 60 Hz

Wattage: 1000 W

9566TRSG-K

GFCI Aspire TR 15A 125V 2P3W SG

UPC: 032664716522

Brand Name: Cooper Wiring Devices

Sub Brand: ASPIRE RF

Voltage Rating: 120 Vac

Frequency Rating: 60 Hz

Wattage: 1000 W



Powering Business Worldwide

9566TRWS

GFCI Aspire TR 15A 125V 2P3W WS

UPC: 032664665615

Brand Name: Eaton

Sub Brand: ARROW HART

Type: (2) Decorator Switch

Special Features: Wiring Type Back and Side Wire, Color Almond

Application: Commercial

Voltage Rating: 120/277 Vac

Amperage Rating: 15 Amp

Number Of Poles: 1

Contact Configuration: Decorator Combination

Action: Switch

Actuator: Paddle

Connection: Screw

Enclosure: Polycarbonate,PVC, Steel Thick Brass Plated Silver Alloy

Mounting: Mounting Straps Are Zinc Plated to for added corrosion resistance

Size: 1.30 In Width X 1.08 In Depth X 4.19 In Height

Operating Temperature: -20 To 60 Deg C

9566TRWS-K

GFCI Aspire TR 15A 125V 2P3W WS

UPC: 032664716539

Brand Name: Eaton

Sub Brand: ARROW HART

Type: (2) Decorator Switch

Special Features: Wiring Type Back and Side Wire, Color Light Almond

Application: Commercial

Voltage Rating: 120/277 Vac

Amperage Rating: 15 Amp

Number Of Poles: 1

Contact Configuration: Decorator Combination

Action: Switch

Actuator: Paddle

Connection: Screw

Enclosure: Polycarbonate,PVC, Steel Thick Brass Plated Silver Alloy

Mounting: Mounting Straps Are Zinc Plated to for added corrosion resistance

Size: 1.30 In Width X 1.08 In Depth X 4.19 In Height

Operating Temperature: -20 To 60 Deg C