



2400 Boston Street, Suite 200, Baltimore, Maryland 21224
Phone: 410-675-2100 or 800-543-3840

Revised: 1/29/16

DAP[®] Roof Asphalt Sealant

- All season
- Wet or dry surface application
- Seal minor roof leaks, fill gaps and repair loose shingles
- Will not run or bubble
- 100% waterproof
- Paintable
- Excellent flexibility and adhesion
- Exterior

Packaging: 10.1 fl. oz. (300 mL)
Color: Black
UPC Number: 70798 18268, 70798 07061

Company Identification:

Manufacturer: DAP Products Inc., 2400 Boston St., Ste. 200, Baltimore, Maryland 21224
Usage Information: Call **1-888-DAP-TIPS** or visit dap.com & click on "Ask the Expert"
Order Information: 800-327-3339
Fax Number: 410-558-1068
Also, visit the DAP website at www.dap.com

Product Description:

DAP[®] ROOF ASPHALT SEALANT is high performance asphalt-based sealant ideal for sealing minor roof leaks, filling gaps and repairing loose shingles. It can be applied to wet or dry surfaces, making it ideal for emergency roof repairs. It offers excellent adhesive and weathering features to outlast oil-based compounds. DAP[®] Roof Asphalt Sealant forms a long-lasting, waterproof seal that resists cracking, crumbling and sagging. Sets tack free in one hour. Paintable. Exterior use.

Suggested Uses:

Ideal for sealing:

- *Corrugated roofing*
- *Asphalt surfaces*
- *Chimneys*
- *Flashing*
- *Shingles, spotting shingle tabs*
- *Gable joints, copings*

Adheres to:

- *Asphalt*
- *Wood*
- *Fiberglass*
- *Metal*
- *Masonry*

Performance Characteristics:

- Resists the damaging effects of ultra-violet light, temperature extremes and weathering that cause hardening, cracking, crumbling of oil-based sealants.
- Wet or dry surface application.
- Will not run or bubble.
- 100% waterproof seal that resists cracking, crumbling and sagging.

Surface Preparation & Application:

1. Remove loose, damaged asphalt or old repair material from surface.
2. Cut nozzle at 45° angle to desired bead size.
3. Puncture inner foil seal.
4. Load cartridge into caulk gun.
5. Fill cracks and gaps with sealant.
6. Sets tack free in less than one hour. A complete cure is attained in two to four weeks, depending on temperature, humidity and depth of fill.
7. Paintable after one hour of application. High quality oil or asphalt-based paint is recommended. One coat may show a slight discoloration. Two coats will provide a clean film.

For Best Results:

- Apply in temperatures between 40°F and 100°F.
- Joint size should not exceed 3/8"wide x 3/8"deep. If joint depth exceeds 3/8", use foam backer rod.
- Store caulk away from extreme heat or cold.

Typical Physical & Chemical Characteristics:

Vehicle:	Asphalt
Solids:	88% by Weight
Density:	13.7lbs/gal
Pigment:	Inert fillers
Tack Free Time:	1 hour
Full Cure Time:	2 to 4 weeks
Odor:	Asphaltic
Consistency:	Gun grade asphaltic compound
Volatile:	Petroleum distillates
Specific Gravity:	1.6
Application Temperature Range:	+40°F to +100°F
Service Temperature Range:	-40°F to +180°F (-40°C to +82°C)
Shelf Life:	12 months @ 70°F
Coverage:	55 linear feet at 3/16" diameter bead
SDS No.:	00010004001

Clean Up & Storage:

Clean up excess uncured sealant with mineral spirits. Excess cured sealant must be cut or scraped away. Do not use mineral spirits to clean skin. Clean hands with warm, soapy water. Store product away from extreme heat or moisture.

Safety:

Warning! Combustible liquid and vapor. Harmful or fatal if swallowed. Contains mineral spirit and asphalt. May cause eye and respiratory tract irritation. May cause dizziness, headache or nausea. Harmful if inhaled or absorbed through skin. May cause skin irritation or burns. Do not breathe vapors. Use only in a well ventilated area. Ensure fresh air entry. Keep away from heat, sparks & flames. Do not smoke. Do not heat this product or

apply to hot surfaces. Avoid eye & skin contact. Wear gloves & eye protection with side shields. Repeated and prolonged overexposure to solvents may cause kidney, liver, heart and permanent brain and nervous system damage. **FIRST AID:** SKIN: Wash thoroughly. EYE: Flood with large quantities of water. INHALATION: Remove to fresh air. INGESTION: DO NOT INDUCE VOMITING. Get medical attention immediately if complications arise from exposure. **For emergencies**, call poison control center at 1-800-222-1222. **KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY.** See product label and Safety Data Sheet (SDS) for additional safety information. You can request an SDS by visiting dap.com or by calling 888-DAP-TIPS.

GUARANTEE:

If product fails to perform when used as directed, within one year of date of purchase, return used container and sales receipt to DAP Products Inc., TCS, 2400 Boston St., Baltimore, MD 21224 for replacement product or sales price refund. DAP is not liable for incidental or consequential damages.