



Representative

Catalog Number: 156LR-G-5240
Product ID: 7TAA121600R0036
UPC Number: 78378663348
Status: Active

15/25kV 200 Amp, Deadbreak Elbow Connector with Test Point Cable Insulation Diameter 0.760 inch to 0.950 inch. Bi-Metal Compression Lug, Conductor Size AWG Compressed Stranded 1/0 /Solid 2/0 /mmSquared 53.49. Includes Elbow Connector Housing, Compression Lug, Probe, Probe Wrench, Bail Assembly, Tube of Lubricant, Installation Instructions, Crimp Chart and V.D. Cap-Peroxide.

UNSPSC Specifications

UNSPSC	39121421 Electrical connector assembly
IGCC	4586 Electrical connector assembly
Brand Name	Elastimold
Type	Deadbreak Elbow Connector
Special Features	Fully shielded, fully submersible molded rubber housing. 100 percent peroxide-cured construction includes insulation and conductive EPDM materials. Provision for hot stick operation, Provision for ground wire connection. Wide cable range with minimum number of sizes. Long bi-metal compression lug is standard. Non-corrosive capacitive voltage test point.
Application	15/25kV, 200 Amp Deadbreak Connection.
Standard	ANSI/IEEE Standard 386.
Size	Cable Insulation Diameter 0.760 inch to 0.950 inch.
Conductor Range	Conductor Size AWG Compressed Stranded 1/0 / Solid 2/0 /mmSquared 53.49.
Material	Housing - EPDM Rubber
Color	Black
Voltage Rating	15/25kV
Amperage Rating	200 Amps
Insulation	Yes
Temperature Rating	-40 Degrees to +65 Degrees C
Environmental Conditions	Fully Submersible
Consist Of	Includes Elbow Connector Housing, Compression Lug, Probe, Probe Wrench, Bail Assembly, Tube of Lubricant, Installation Instructions, Crimp Chart and V.D. Cap-Peroxide.

Packaging

Outer Quantity	15
Weight Uom	1.89 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com