



Representative

**Catalog Number:** K676LRTP-M2400-DRG  
**Product ID:** 7TAA122400R0163  
**UPC Number:** 07511431309  
**Status:** Active

900 Amp, 25kV, Deadbreak, Stick-Op Connector Kit with Test Point, With Insulated Cap. Cable Insulation Diameter 1.370 inch to 1.630 inch. Aluminum Compression Lug. Conductor Size AWG Compressed Stranded 1000.

#### North American Specifications (UNSPSC)

UNSPSC	39121421 Electrical connector assembly
IGCC	4586 Electrical connector assembly
Brand Name	Elastimold
Type	Stick Op Reducing Tap Plug Connector with Test Point
Special Features	Reducing Tap Plug 900 to 200 Amps. Test Point. Provides an External Visible Break by Hotstick Removal of the Elbow.
Application	Connect 900 Amp interface to 200 Amp Loadbreak Tap
Standard	ANSI/IEEE Standard 386
Conductor Range	Conductor Size AWG Compressed Stranded 1000.
Material	Housing - EPDM Rubber
Color	Black
Enclosure	Yes, EPDM Rubber
Voltage Rating	25kV
Amperage Rating	900/200 Amps
Insulation	Yes, EPDM Rubber
Temperature Rating	-40 degrees to +65 degrees Celsius
Environmental Conditions	All Weather

#### Packaging

Outer Quantity	1
Outer Dimensions (inches)	14x9x11
Weight Uom	1 lbs. Each

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
 MS 3B-50  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)