

# PRODUCT SPECIFICATIONS

## Arc Flash Web Loop Full Body Harness

## #7051L

### Features

- Dorsal Web Loop; Nylon Webbing;
- 5-point adjustability.
- Mating Buckle Legs, Chest and Torso Adjusters
- Leather Insulated buckles and adjusters.

### Material Specifications

<b>Webbing:</b>	<i>Nomex®/Kevlar®; Min. 7,000 lbs. tensile strength</i>
<b>D-Rings:</b>	<i>Insulated Alloy Steel; Min. 5,000 lbs. tensile strength</i>
<b>Buckles/Adjusters:</b>	<i>Insulated Alloy Steel; Min. 5,000 lbs. tensile strength</i>

### Performance Specifications

<b>Tensile Strength:</b>	<i>Min. 5,000 lbs.</i>
<b>Max. Capacity:</b>	<i>425 lbs. To maintain ANSI Z359 compliance, limit total user weight to 310lbs</i>

### Relevant Standards

<b>OSHA:</b>	<i>CFR1926.502, CFR1910.66</i>
<b>ANSI:</b>	<i>A10.32-2004, Z359.1-2007, Z359.12-2009</i>
<b>ASTM:</b>	<i>ASTM F887-10</i>

### Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Never attach a Shock Absorbing Lanyard to the front, side or shoulder D-Rings.



FallTech 1306 S. Alameda St. Compton, CA 90221 Tele: 323-752-0066 www.falltech.com

EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.