


# **Standard Construction Features**

Belt Type: Synchronous Core Material: Oil & Heat Resistant (chloroprene) Cord/Tensile: Fiberglass Jacket: Nylon



### **Belt Section Dimensions**

Tooth	Pitch	h <sub>s</sub>	h <sub>t</sub>	
Type	(in)	(in)	(in)	
TRAP	1/2	0.155	0.090	

## **Belt Dimensions**

Pitch Length	No.	Width
(in)	Teeth	(in)
75.00 + 0.036 - 0.036	150	1.500 + 0.030 - 0.050

#### Measuring Information

Y (in)	T (lbf)	No. Teeth	O.D. (in)	Pitch Circum. (in)	Radial Runout (in)	Axial Runout (in)	PLD 2a (in)
32.50 + 0.018 + 0.018	221	20	3.13	10.00	0.0005	0.0010	0.054

#### Pitch Circumference DesignView™ Belt Information Sheet Belt Pitch Line Belt Tooth outside diameter diamete Created 28 Jun 2017 by Gates Created for **PowerGrip Timing - H** Lev Groove Gates Product Number **Customer Part Number** The length shall be measured by placing the belts on two pulleys of equal diameters that have been grooved in accordance with standard specifications and rotated at least three complete turns with the specified tension so that each strand receives half the total tension. The length will be that length obtained by adding the Pitch Circumference of one pulley to twice the center distance (dimension 'Y'). 9257-3316 750H150

Application Version: 1.1.24 Database Version: 1.1.00