

Twist-Lock® Devices Safety-Shroud® Twist-Lock®– 20A and 30A Safety-Shroud® Accessory

HUBBELL



Features

- Add-A-Shroud® devices allow conversion of existing 20A and 30A 3 to 5 wire Hubbell Insulgrip® Twist-Lock® devices to a Safety-Shroud® Twist-Lock® plug
- The Safety-Shroud® Twist-Lock® plug permits engagement with the Hubbell Mechanical Interlock Enclosure which virtually prevents make and break under load
- These devices provide a convenient and cost-effective way to convert existing Hubbell Insulgrip® Twist-Lock® plugs to Safety-Shroud® Twist-Lock® plugs

Ordering Information

Description	Device Color	UPC	Catalog Number
Add-a-Shroud for 3 Pole 4 Wire and 4 Pole 5 Wire Insulgrip® Devices	White	783585174150	HBLSS45



Accessories

Plug Accommodation	21 Amp & 30 Amp, 4 & 5 Wire Twist-Lock®
--------------------	---

Resources

[eCatalog](#)

Specifications

Shroud	Nylon
Screws	Zinc plated steel

Performance

Environmental

Flammability	HB or better
Operating Temperatures	Maximum Continuous 75°C Minimum -40°C (w/o impact)

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

