

**Catalog Number:** AB12-M20  
**Product ID:** 7TCA298010R0044  
**EAN Number:** 05020963036903  
**Status:** Active

Sealed Conduit Fitting, Straight, Compression Type, Conduit Size NC12/NW10, M20 Thread, Operating Temperature -40 to 120 Degrees Celsius, RoHS Compliant, IP67, 68 Rating, Very High UV Protection, Polyamide (Nylon), Black

#### North American Specifications (UNSPSC)

UNSPSC	39121311 Electrical fittings
IGCC	4441 Electrical fittings
Brand Name	Harnessflex
Type	Sealed Conduit Compression Fitting
Special Features	Self Extinguishing, Low Smoke Toxicity, and Halogen Free
Application	Designed to Help Maintain System Integrity for Conduit Systems
Standard	ADR Approved (with NC conduits only) , RoHS
Size	Conduit Size NC12/NW10
Material	Polyamide/Nylon
Insulation Class	IP67, IP68
Color	Black
Connection	Straight, M20 Thread
Temperature Rating	-40 to 120 Degrees C

#### European Specifications (ETIM)

ETIM	EC001176 Screw connection for corrugated plastic hose
Nominal diameter	12mm
Nominal size in inch	3/8 inch
Degree of protection (IP)	IP68
Model	Straight
Revolving thread	N
Construction type	External thread
Type of connection	Thread
Thread type	Metric
Thread connection size	M20 x 1.5
Thread length	14mm
Total length	27mm
Total height	37mm
Material	Polyamide
Colour	Black

#### Packaging

Inner Quantity	10
Outer Quantity	300
Outer Dimensions (inches)	14x14x6
Weight Uom	0.02 lbs. Each

#### Header

3D Model [Available on Website](#)

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120

T&B Technical Support  
 MS 3B-50  
 860 Ridge Lake Blvd.

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289

