

Catalog Number: AB16-M16
Product ID: 7TCA298010R0050
EAN Number: 05020963036880
Status: Active

Sealed Conduit Fitting, Straight, Compression Type, Conduit Size NC16/NW13, M16 Thread, Operating Temperature -40 to 120 Degrees Celsius, RoHS Compliant, IP67, 68 Rating, Very High UV Protection, Polyamide (Nylon), Black

North American Specifications (UNSPSC)

UNSPSC	39121311 Electrical fittings
IGCC	4441 Electrical fittings
Brand Name	Harnessflex
Type	Sealed Conduit Compression Fitting
Special Features	Self Extinguishing, Low Smoke Toxicity, and Halogen Free
Application	Designed to Help Maintain System Integrity for Conduit Systems
Standard	ADR Approved (with NC conduits only) , RoHS
Size	Conduit Size NC16/NW13
Material	Polyamide/Nylon
Insulation Class	IP67, IP68
Color	Black
Connection	Straight, M16 Thread
Temperature Rating	-40 to 120 Degrees C

European Specifications (ETIM)

ETIM	EC001176 Screw connection for corrugated plastic hose
Nominal diameter	16mm
Nominal size in inch	1/2 inch
Degree of protection (IP)	IP68
Model	Straight
Revolving thread	N
Construction type	External thread
Type of connection	Thread
Thread type	Metric
Thread connection size	M16 x 1.5
Thread length	12mm
Total length	27mm
Total height	35mm
Material	Polyamide
Colour	Black

Packaging

Outer Quantity	10
Outer Dimensions (inches)	6x1x7
Weight Uom	0.02 lbs. Each

Header

3D Model	Available on Website
----------	----------------------

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
 www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email:techsupport@tnb.com