

**Catalog Number:** AB20-M20-90  
**Product ID:** 7TCA298010R0061  
**EAN Number:** 05020963021558  
**Status:** Active

Sealed Conduit Fitting, 90 Degree Elbow, Compression Type, Conduit Size NC20/NW17, M20 Thread, Operating Temperature -40 to 120 Degrees Celsius, RoHS Compliant, IP67, 68 Rating, Very High UV Protection, Polyamide (Nylon), Black

**North American Specifications (UNSPSC)**

UNSPSC	39121311 Electrical fittings
IGCC	4441 Electrical fittings
Brand Name	Harnessflex
Type	Sealed Conduit Compression Fitting
Special Features	Self Extinguishing, Low Smoke Toxicity, and Halo-gen Free
Application	Designed to Help Maintain System Integrity for Conduit Systems
Standard	ADR Approved (with NC conduits only) , RoHS
Size	Conduit Size NC20/NW17
Material	Polyamide/Nylon
Insulation Class	IP67, IP68
Color	Black
Connection	90 Degree, M20 Thread
Temperature Rating	-40 to 120 Degrees C

**European Specifications (ETIM)**

ETIM	EC001176 Screw connection for corrugated plastic hose
Nominal diameter	20mm
Nominal size in inch	1/2 inch
Degree of protection (IP)	IP68
Model	90°-elbow
Revolving thread	N
Construction type	External thread
Type of connection	Thread
Thread type	Metric
Thread connection size	M20 x 1.5
Thread length	13mm
Material	Polyamide
Colour	Black

**Packaging**

Inner Quantity	10
Outer Quantity	120
Outer Dimensions (inches)	14x14x6
Weight Uom	0.03 lbs. Each

**Header**

3D Model	Available on Website
----------	----------------------

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
860 Ridge Lake Blvd.  
Memphis, TN 38120  
www.tnb.com

T&B Technical Support  
MS 3B-50  
860 Ridge Lake Blvd.  
Memphis, TN 38120

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email:techsupport@tnb.com