

Catalog Number: AB20-PG16-90
Product ID: 7TCA298010R0064
EAN Number: 05020963035852
Status: Active

Sealed Conduit Fitting, 90 Degree Elbow, Compression Type, Conduit Size NC20/NW17, PG16 Thread, Operating Temperature -40 to 120 Degrees Celsius, RoHS Compliant, IP67, 68 Rating, Very High UV Protection, Polyamide (Nylon), Black

North American Specifications (UNSPSC)

| | |
|--------------------|--|
| UNSPSC | 39121311 Electrical fittings |
| IGCC | 4441 Electrical fittings |
| Brand Name | Harnessflex |
| Type | Sealed Conduit Compression Fitting |
| Special Features | Self Extinguishing, Low Smoke Toxicity, and Halogen Free |
| Application | Designed to Help Maintain System Integrity for Conduit Systems |
| Standard | ADR Approved (with NC conduits only) , RoHS |
| Size | Conduit Size NC20/NW17 |
| Material | Polyamide/Nylon |
| Insulation Class | IP67, IP68 |
| Color | Black |
| Connection | 90 Degree, PG16 Thread |
| Temperature Rating | -40 to 120 Degrees C |

European Specifications (ETIM)

| | |
|---------------------------|---|
| ETIM | EC001176 Screw connection for corrugated plastic hose |
| Nominal diameter | 20mm |
| Nominal size in inch | 1/2 inch |
| Degree of protection (IP) | IP68 |
| Model | 90°-elbow |
| Revolving thread | N |
| Construction type | External thread |
| Type of connection | Thread |
| Thread type | Other |
| Thread connection size | PG16 |
| Thread length | 12mm |
| Material | Polyamide |
| Colour | Black |

Packaging

| | |
|---------------------------|----------------|
| Outer Quantity | 10 |
| Outer Dimensions (inches) | 1x1x1 |
| Weight Uom | 0.03 lbs. Each |

Header

| | |
|----------|----------------------|
| 3D Model | Available on Website |
|----------|----------------------|

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
 www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email:techsupport@tnb.com