



Representative

**Catalog Number:** AL 500 NTN  
**Product ID:** 7TAA262020R0067  
**UPC Number:** 78378669385  
**Status:** Active

Aluminum Tin-Plated Two-Hole NEMA Lugs - straight lug, concentric 500 and 477 compact 500-600, ACSR 397.5 (26/7) and 477 (18/1), installing dies 106A,300,317,1 5/16,14A,15A

### UNSPSC Specifications

UNSPSC	39121448 Wire or cable compression connector
IGCC	4668 Wire or cable compression connector
Brand Name	Blackburn
Type	Aluminum Two-Hole NEMA Lugs
Special Features	Dual-rated. Use with Aluminum and Copper conductors. Prefilled with oxide inhibitor to prevent oxidation and keep out moisture. All lugs marked with conductor sizes and die reference for easy identification.
Application	General purpose lugs for Aluminum and Copper terminations.
Standard	ANSI C119.4
Size	Length 8-1/4 inches
Conductor Range	500
Material	Aluminum
Finish	Tin-Plated

### Packaging

Outer Quantity	25
Outer Dimensions (inches)	8.1x6.7x7.3
Weight Uom	0.61 lbs. Each

### Documents / Support Tools

SDS US 1	sds-00041-tb2
Technical Data Sheet CA	Available on Website

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
 8155 T&B Blvd.  
 Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
 MS 3B-50  
 8155 T&B Blvd.  
 Memphis, TN 38125

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)