



Family

**Catalog Number:** **FSS 1000 L**  
**Product ID:** 7TAA260080R0036  
**UPC Number:** 78378672499  
**Status:** Active

Flood-Seal Insulating Covers-FSS Series, copper conductor range 2-1500, aluminum conductor range 2-1000, cable insulation diam range .370-1.600, length 18-1/8 inch

**UNSPSC Specifications**

UNSPSC	39121468 Input output connector cover
IGCC	4698 Input output connector cover
Brand Name	Homac
Type	Insulating Cover - End Caps
Special Features	Sizes for most conductors, perfect for Copper or Aluminum Conductors ranging from #14 AWG to 1500 kcmil. Easy to Install. Waterproof. Eliminate taping to significantly reduce labor and material cost of splice preparation.
Application	Watertight Splice Applications. Rated 600 Volts - built for Heavy-Duty Loads.
Standard	RUS Accepted
Material	Santoprene Rubber
Color	Black
Length	18-1/8 inch
Conductor Range	Aluminum and Copper #2 to 1000 kcmil

**Packaging**

Outer Quantity	25
Outer Dimensions (inches)	27.9x13.3x10.4
Weight Uom	1.05 lbs. Each

**Documents / Support Tools**

SDS US 1	sds-00048-tb2
SDS US 2	
SDS US 3	
Technical Data Sheet CA	Available on Website

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
www.tnb.com

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email:techsupport@tnb.com