



Representative

Catalog Number: **FSS 1000**
Product ID: 7TAA260080R0034
UPC Number: 78378672497
Status: Active

Flood-Seal Insulating Covers-FSS Series, copper conductor range 2-1000, aluminum conductor range 2-1000, cable insulation diam range .370-1.600, length 10 inch

UNSPSC Specifications

| | |
|------------------|---|
| UNSPSC | 39121468 Input output connector cover |
| IGCC | 4698 Input output connector cover |
| Brand Name | Homac |
| Type | Insulating Cover - End Caps |
| Special Features | Sizes for most conductors, perfect for Copper or Aluminum Conductors ranging from #14 AWG to 1500 kcmil. Easy to Install. Waterproof. Eliminate taping to significantly reduce labor and material cost of splice preparation. |
| Application | Watertight Splice Applications. Rated 600 Volts - built for Heavy-Duty Loads. |
| Standard | RUS Accepted |
| Material | Santoprene Rubber |
| Color | Black |
| Length | 10 inch |
| Conductor Range | Aluminum and Copper #2 to 1000 kcmil |

Packaging

| | |
|---------------------------|-----------------|
| Outer Quantity | 20 |
| Outer Dimensions (inches) | 18x14.3x9.2 |
| Weight Uom | 78 lbs. per 100 |

Documents / Support Tools

| | |
|-------------------------|----------------------|
| SDS US 1 | sds-00048-tb2 |
| SDS US 2 | |
| SDS US 3 | |
| Technical Data Sheet CA | Available on Website |

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com