



Representative

Catalog Number: **FSS 500**
Product ID: 7TAA260080R0051
UPC Number: 78378672515
Status: Active

Flood-Seal Insulating Covers-FSS Series, copper conductor range 14-500, aluminum conductor range 14-500, cable insulation diam range .150-1.175, length 4-7/8 inch

North American Specifications (UNSPSC)

UNSPSC	39121468 Input output connector cover
IGCC	4698 Input output connector cover
Brand Name	Homac
Type	Insulating Cover - End Caps
Special Features	Sizes for most conductors, perfect for Copper or Aluminum Conductors ranging from #14 AWG to 1500 kcmil. Easy to Install. Waterproof. Eliminate taping to significantly reduce labor and material cost of splice preparation.
Application	Watertight Splice Applications. Rated 600 Volts - built for Heavy-Duty Loads.
Standard	RUS Accepted. UL E100543. UL E9809
Material	Santoprene Rubber
Color	Black
Length	4-7/8 inch
Conductor Range	#14 to 500 kcmil

Packaging

Outer Quantity	100
Outer Dimensions (inches)	15x12.5x15.5
Weight Uom	18 lbs. per 100

Documents / Support Tools

SDS US 1	sds-00048-tb2
SDS US 2	
SDS US 3	
Technical Data Sheet CA	Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com