



Representative

**Catalog Number:** FYU 6  
**Product ID:** 7TAA260520R0031  
**UPC Number:** 78378672761  
**Status:** Active

Flood-Seal Street and Highway Lighting Mechanical Fuse and Disconnect Kits - Y Line mechanical run Compression Kits, fused, conductor range main 14-2 tap 14-6

### North American Specifications (UNSPSC)

UNSPSC	39121421 Electrical connector assembly
IGCC	4586 Electrical connector assembly
Brand Name	Homac
Type	Break-Away Streetlight Kits
Special Features	EPDM Flood-Seal Housing ensures a fully insulated, watertight, and submersible connection. Beakaway design separates under tension so wires don't break. Safe separations to ensure fuse or connecting link stays in load side when separated. Re-Enterable to enable sectionalizing. Matching Ampacity Rating - run or feeder lugs have the same ampacity rating as the cable, up to 2/0. Y-Type Mechanical Run Compression Taps use a 1/8 inch Hex wrench for easy Installation.
Application	Rated 600V, 30 Amps Maximum, perfect for heavy-duty applications.
Connection	Mechanical
Conductor Range	main 14-2 tap 4-6
Number Of Conductors	3
Material	Aluminum and Copper, EPDM Rubber Housing
Color	Black
Voltage Rating	600 Volts
Amperage Rating	30 Amps
Insulation	Yes
Environmental Conditions	Watertight
Consist Of	Flood Seal Housing, Fuse Clips, Dowel and Silicone Lubricant. Fuse not Included.

### Packaging

Outer Quantity	25
Outer Dimensions (inches)	13.4x8.3x7.8
Weight Uom	34 lbs. per 100

### Documents / Support Tools

Technical Data Sheet CA	Available on Website
-------------------------	----------------------

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
 8155 T&B Blvd.  
 Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
 MS 3B-50  
 8155 T&B Blvd.  
 Memphis, TN 38125

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)