



Actual

**Catalog Number:** SLK-M  
**Product ID:** 7TAA260520R0067  
**UPC Number:** 78378675227  
**Status:** Active

Flood-Seal Street and Highway Lighting Mechanical Fuse and Disconnect Kits-In-Line, fused, conductor range stranded 12,10,8,6,4 and solid 12,10,8,6,4

### North American Specifications (UNSPSC)

UNSPSC	39121421 Electrical connector assembly
IGCC	4586 Electrical connector assembly
Brand Name	Elastimold
Type	Breakaway Street Light Kit
Special Features	EPDM Rubber Housing Ensures Fully Insulated, Watertight and Submersible Connection. Safe Separations, Fuse or Connecting Link Stays in Load Side when Separated. Dual-Rated and Approved. Rated for 600 Volts, 30 Amp Maximum.
Application	Heavy Duty Applications
Conductor Range	Aluminum/Copper Stranded 12, 10, 8, 6, 4/ Solid 12, 10, 8, 6, 4
Material	EPDM Rubber
Voltage Rating	600 Volts
Amperage Rating	30 Amps
Insulation	Yes
Environmental Conditions	Submersible, Watertight

### Packaging

Outer Quantity	25
Outer Dimensions (inches)	12x6.25x9
Weight Uom	14.5 lbs. per 100

### Documents / Support Tools

SDS US 1	sds-00048-tb2
Technical Data Sheet CA	Available on Website

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
 8155 T&B Blvd.  
 Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
 MS 3B-50  
 8155 T&B Blvd.  
 Memphis, TN 38125

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)