



Actual

**Catalog Number:** SL 3-2 K  
**Product ID:** 7TAA260520R0051  
**UPC Number:** 78378675262  
**Status:** Active

Aluminum Flood-Seal Mechanical Splice Three-Wire Kits, conductor range 4-14CU/2-14AL, 3 outlets

**UNSPSC Specifications**

UNSPSC	39121449 Wire or cable compression splice
IGCC	4669 Wire or cable compression splice
Brand Name	Homac
Type	Aluminum Flood-Seal Compression Splice Kits
Special Features	Prefilled with Oxide-Inhibitor to prevent oxidation and keep out moisture. Dual-Rated. Approved for a wide range of aluminum or copper conductors. EPDM Rubber Splice Covers Ensure a Fully Insulated, Watertight Repair Splice - There is no Taping, Hat Shrink or Masic Required. Sized for most conductors. Perfect for repairing any 2-,3- or 4-wire installation.
Size	3 inch overall Length
Connection	Mechanical
Conductor Range	#4=#14 Copper, 2-14 Aluminum
Material	Aluiminum with EDPM Rubber Cover

**Packaging**

Outer Quantity	25
Outer Dimensions (inches)	13x8x7.5
Weight Uom	20.5 lbs. per 100

**Documents / Support Tools**

SDS US 1	sds-00041-tb2
Technical Data Sheet CA	Available on Website

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
www.tnb.com

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email:techsupport@tnb.com