



Actual

**Catalog Number:** USK 350  
**Product ID:** 7TAA260100R0010  
**UPC Number:** 78378675557  
**Status:** Active

Aluminum Flood-Seal Mechanical Splice Two-Wire Kits, conductor range 6-350 connector length 2-9/16 inch, screws per side 1

### UNSPSC Specifications

UNSPSC	39121421 Electrical connector assembly
IGCC	4586 Electrical connector assembly
Brand Name	Homac
Type	Mechanical Splice
Special Features	Prefilled with Oxide Inhibitor to prevent Oxidation and keep out Moisture. Dual-Rated and approved for use with Aluminum and Copper Conductors. EPDM Rubber Splice Covers ensure a fully insulated, watertight repair splice. No Taping, Heat-Shrink or Mastic needed.
Application	Repair Splice
Size	2-9/16 inch connector
Connection	Mechanical
Conductor Range	6 to 350
Number Of Conductors	2
Material	Aluminum Connector, EPDM Cover
Insulation	Yes

### Packaging

Outer Quantity	25
Outer Dimensions (inches)	11.4x10.3x10.6
Weight Uom	40.5 lbs. per 100

### Documents / Support Tools

SDS US 1	sds-00041-tb2
Technical Data Sheet CA	Available on Website

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
 8155 T&B Blvd.  
 Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
 MS 3B-50  
 8155 T&B Blvd.  
 Memphis, TN 38125

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)