

Catalog Number: USK 500 L
Product ID: 7TAA260100R0020
UPC Number: 78378675567
Status: Active

Aluminum Flood-Seal Mechanical Splice Two-Wire Kits, conductor range 2-500 connector length 7-1/2 inch, screws per side 2



Actual

UNSPSC Specifications

UNSPSC	39121421 Electrical connector assembly
IGCC	4586 Electrical connector assembly
Brand Name	Homac
Type	Mechanical Splice
Special Features	Prefilled with Oxide Inhibitor to prevent Oxidation and keep out Moisture. Dual-Rated and approved for use with Aluminum and Copper Conductors. EPDM Rubber Splice Covers ensure a fully insulated, watertight repair splice. No Taping, Heat-Shrink or Mastic needed.
Application	Repair Splice
Size	7-1/7 inch connector
Connection	Mechanical
Conductor Range	#2 to 500
Number Of Conductors	2
Material	Aluminum Connector, EPDM Cover
Insulation	Yes

Packaging

Outer Quantity	15
Outer Dimensions (inches)	17.75x14.25x9
Weight Uom	1.57 lbs. Each

Documents / Support Tools

SDS US 1	sds-00044-tb2
Technical Data Sheet CA	Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com