



## Overhead Connectors and Covers

T&B Catalog Number:

X 1 U 4020

UPC Number:

78378675966

Status:

Active

Description:

Uninsulated Aluminum Service Entrance Compression Splices - 840 die series, Conductor A: Pink, - Solid Aluminum, - Solid Copper, 4/0 Stranded, 4/0 ACSR, Conductor B: Gray, 3/0 Solid Aluminum, - Solid Copper, 2/0 Stranded, 2/0 ACSR.

### Features

Constructed from Aluminum. Provides high conductivity.

Solid center barriers enable quick wire positioning, proper distribution of inhibitor around the wire and current equalization on stranded conductors.

Prefilled with Oxide Inhibitor to prevent oxidation and keep out moisture.

Splices are marked with strip lengths, die codes, and compression locations for easy identification and easy installation.

### General

Style	Service Entrance Compression Splices
Material	Aluminum
Conductor A Color	Gray
Conductor B Color	Gray

### Dimension Information

Conductor A Wire Size Str	4/0
Conductor B Solid - AL	3/0
Conductor B Wire Size Str	2/0
Conductor Range A ACSR	4/0
Conductor Range B ACSR	2/0

### Notes

When using EE1 11A die, space compressions 1/8" apart.

When installing with UT5 tool, use H5 (upper), and H6 (lower) dies.

When installing with a hydraulic tool, use 76 (2) die.

### Certifications

RUS	Y
-----	---

For further technical assistance, please contact us...

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
www.tnb.com

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email:techsupport@tnb.com