



Overhead Connectors and Covers

T&B Catalog Number:

X 1 U 4040

UPC Number:

78378675969

Status:

Active

Description:

Uninsulated Aluminum Service Entrance Compression Splices - 840 die series, Conductor A: Pink, - Solid Aluminum, - Solid Copper, 4/0 Stranded, 4/0 ACSR, Conductor B: Pink, - Solid Aluminum, - Solid Copper, 4/0 Stranded, 4/0 ACSR.

Features

Constructed from Aluminum. Provides high conductivity.

Solid center barriers enable quick wire positioning, proper distribution of inhibitor around the wire and current equalization on stranded conductors.

Prefilled with Oxide Inhibitor to prevent oxidation and keep out moisture.

Splices are marked with strip lengths, die codes, and compression locations for easy identification and easy installation.

General

Style	Service Entrance Compression Splices
Material	Aluminum
Conductor A Color	Pink
Conductor B Color	Pink

Dimension Information

Conductor A Wire Size Str	4/0
Conductor B Wire Size Str	4/0
Conductor Range A ACSR	4/0
Conductor Range B ACSR	4/0

Notes

When using EE1 11A die, space compressions 1/8" apart.

When installing with UT5 tool, use H5 (upper), and H6 (lower) dies.

When installing with a hydraulic tool, use 76 (2) die.

Certifications

RUS	Y
-----	---

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com