

BL-WA22/WA25

Superbay Series

The WA22 22" acrylic is designed as the economical solution to all non-impact applications. Clear lighting grade acrylic allows about 20% uplight for a well-lit application.

WA25 acrylic reflector is designed for 15 to 30 foot mounting heights in areas that call for efficient three-dimensional illumination as well as good looks.

All reflectors have field-adjustable reflector brackets for medium to wide lighting distributions. Use coated lamp for best performance. Follow ambient temperature guidelines for long life.

Suitable for damp location.
Minimum 90°C supply conductors.



ORDERING INFORMATION

BL	-		-		-		-	EX
SERIES		SOURCE		VOLTAGE		COLOR		SOCKET
BL Superbay Series		S High Pressure Sodium P Pulse Start Metal Halide		5 480V 6 Tri-Tap® (120, 277, 347V) 8 Quad Tap® (120, 208, 240, 277V) F 347V		WH White (standard) GR Gray		EX Pink exclusionary socket. Required for PSMH
WATTAGE						OPTICS		
175	175w PSMH only					WA22	22" Wide acrylic reflector	
250	250w PSMH or HPS					WA25	25" Wide acrylic reflector	
320	320w PSMH only							
400	400w PSMH or HPS							

ACCESSORIES - Order Separately

Catalog Number	Description
WA2-ENC	Bottom enclosure
WA22-CDL	Conical bottom enclosure
WA22-DLR	Drop lens bottom enclosure
WA25-DLR	Drop lens bottom enclosure

Note: Bottom enclosures are required unless lamps designated as "suitable for open use" are used

Note: Options must be added as suffix to catalog number; Accessories must be ordered separately

Max Ambient Temperature Chart		
Wattage	Open	Enclosed
250 PSMH/HPS	55°C	55°C
320 PSMH	55°C	55°C
400 PSMH	55°C	55°C

For complete temperature information, see page 441.

For a complete list of Options and Accessories see pages 437 to 445.

LEG MOUNT WA22	A	B	C	D	E	F
Quick-On®	24 7/8" - 27 1/8"	22 1/2"	8 5/8"	14"	9 1/2"	1 1/8"
Slick-On®	632 - 689 mm	572 mm	219 mm	356 mm	241 mm	29 mm

FLUSH MOUNT WA22	A	B	C	D	E	F
Quick-On®	22 5/8"	22 1/2"	8 5/8"	14"	9 1/2"	1 1/8"
Slick-On®	575 mm	572 mm	219 mm	356 mm	241 mm	29 mm

LEG MOUNT WA25	A	B	C	D	E	F
Quick-On®	25 7/16" - 27 11/16"	25 3/8"	8 5/8"	14 5/8"	9 1/2"	1 1/8"
Slick-On®	646 - 686 mm	645 mm	219 mm	371 mm	241 mm	29 mm

FLUSH MOUNT WA25	A	B	C	D	E	F
Quick-On®	23 1/4"	25 3/8"	8 5/8"	14 5/8"	9 1/2"	1 1/8"
Slick-On®	591 mm	645 mm	219 mm	371 mm	241 mm	29 mm

