

Engineered to strip every wire right

		Kir	netic™ Reflex™	T [®] -Stripper W	ire Stripper	
	Th gri mu pre	netic [™] Super W e ergonomic des p wicks away p iscle fatigue. Th ecision stripping curacy in the ind -Stripper Wire	d Thumb Valley" re stripper in the sign and patentee erspiration and e Thumb Valley" holes promote dustry. Stripper	d Santoprene™ reduces ^M guide and		 Thumb Valley™ Protection Pocket Locket Locking Hasp Shear Cut Bolt Cutters Santoprene™ Ergo Handles
De En gr	flex [™] Premium T [*] -Stripper W esigned for total-comfort and wi gonomic handles fit an electricia p and reduces hand fatigue. Tex sistant sleeves cushion thumb a	ue. Features 6/3 utting holes and ge. Tire Stripper re stripping. In's natural tured, slip-	2 and 8/32	Locking Pawl Bolt Cutting Extended Textured Comfort Sense Userline	 Pocket Locket Locking Hasp Shear Cut Bolt Cutters Santoprene[™] Curved Handles 	
the added convenilocking pawl. Curv accommodate high T*-Stripper Wire Stripper The industry standard for almost 5 lightweight and easy to use. Feature knife-type blades, built-in looping blades, b	per Wire Stripper features with ence of bolt-cutting holes and red comfort-grip handles n-volume wire stripping.	 Locking Pawl Bolt Cutting Comfort Curved Handles 	• Extended Textured • Ergo Handles	• Ergo Handles		
T°-Stripper Wire Stripper Selection Guide 6 8 10 12 14 16 18 20 22 24 26 28 30	#45-100's	#45-300's	#45-400's	#45-600's	#45-700's	#45-900's
8 10 12 14 16 18 20 22 24 26 28 30 32 % <	45-125	45-317	45-417			
14 16 18 20 22 24 Solid 16 18 20 22 24 26 Solid	45-121	45-316	45-416	45-616	45-716	-
10 12 14 16 18 Signature 12 14 16 18 Signature Signature	45-120	-	45-415	—	45-715	45-915
8 10 12 14 16 Solid		45-315	_	45-615	_	_
6 8 10 12 14 Solid 8 10 12 14 16 Stranded	45-124	45-318	45-418	45-618	45-718	45-918
T*-Cutter	45-123	_	_	_	_	_

Static Disp



- Non-slip Santoprene[™] textured grips
- Plier nose for holding and twisting wires
- Slide lock for safety and storage
- Thumb and finger valley makes stripping easier and more accurate
- Shear-Cut[™] bolt cutters

Description	Solid	Stranded	Cat. No.
Kinetic Super™ Wire Stripper	10-18	12-20	45-715
Kinetic Super [™] Wire Stripper	14-24	16-26	45-716
Kinetic Super [™] Wire Stripper	6-14	8-16	45-718

Reflex™ Premium T®-Stripper Wire Strippers



- Ergonomic design for maximum comfort
- Curved handles reduce wrist fatigue
- Sleeves that extend to stripping head to cushion thumb and fingers
- Textured, no-slip sleeves provide a sure, easy grip

Description	Solid	Stranded	Cat. No.
Reflex™ Premium T®-Stripper Wire Stripper	10-18	12-20	45-415
Reflex [™] Premium T [®] -Stripper Wire Stripper	14-24	16-26	45-416
Reflex [™] Premium T [®] -Stripper Wire Stripper	22-30	24-32	45-417
Reflex [™] Premium T [®] -Stripper Wire Stripper	6-14	8-16	45-418
Reflex [™] Premium T [®] -Stripper – Metric	0.5mm ² -4.0mm ²		45-425-341
Reflex™ Premium T [®] -Cutter	Cutter		45-423

Kinetic[™] Reflex[™] T[®]-Stripper **Wire Strippers**



- Non-slip Santoprene[™] textured grips and thumb rest
- Plier nose for holding and twisting wires
- Slide lock for safety and storage
- Thumb and finger valley makes stripping easier and more accurate
- Shear-Cut[™]" bolt cutters

Description	Solid	Stranded	Cat. No.
Kinetic™ Reflex™ T®-Stripper Wire Stripper	10-18	12-20	45-915
Kinetic™ Reflex™ T [®] -Stripper Wire Stripper	6-14	8-16	45-918

Reflex[™] Super T[®]-Stripper Wire Strippers



- 6/32 and 8/32 self-chasing screw-cutting holes
- Locking pawl for safe storage
- Ergonomic design for maximum comfort
- Curved handles reduce wrist fatigue
- Sleeves that extend to stripping head to cushion thumb and fingers
- Textured sleeves with extra cushioning for added comfort

Description	Solid	Stranded	Cat. No.
Reflex™ Super T [®] -Stripper Wire Stripper	8-16	10-18	45-615
Reflex™ Super T [®] -Stripper Wire Stripper w/static dissipative grips	14-24	16-26	45-616
Reflex™ Super T [®] -Stripper Wire Stripper	8-14	8-16	45-618
Reflex™ Super 12/2 & 14/2 NM Cable T®-Stripper Wire Stripper	12-2 and 14-2		45-621
Reflex™ Super 12/3 & 14/3 NM Cable T®-Stripper Wire Stripper	12-3 and 14-3		45-622





T®-Stripper Wire Strippers

- Form-ground, knife-type blades for accurate, easy stripping without nicking insulation
- Built-in wire cutter and looping holes
- Convenient plier nose for extra gripping strength
- Laser-etched wire gauge for easy-to-read visibility
- Spring-loaded automatic opening
- Corrosion-resistant, black oxide finish
- Tough steel construction

Description	Solid	Stranded	Cat. No.
T®-5 T®-Stripper Wire Stripper	10-18	12-20	45-120
T®-6 T®-Stripper Wire Stripper	14-24	16-26	45-121
T®-7 T®-Stripper Wire Stripper	22-30	24-32	45-125
T®-8 T®-Stripper Wire Stripper	6-14	8-16	45-124
T®-Stripper Wire Stripper – Metric	0.75-	0.75-6mm ²	
T®-Stripper Wire Stripper – Metric	0.5-4	0.5-4mm ²	

NM Cable T[®]-Stripper Wire Strippers

- Easy, one-step stripping of outer jacket of NM cable – no slitting required
- Versatility to strip, cut and loop conductor wires with precision and ease
- Stripping holes for 12 or 14 AWG solid wire
- Locking pawl for safe storage

Description	Cat. No.
14/2 NM Cable T [®] -Stripper Wire Stripper	45-248
12/2 NM Cable T [®] -Stripper Wire Stripper	45-249
Reflex™ Super 12/2 & 14/2 NM Cable T®-Stripper Wire Stripper	45-621
Reflex™ Super 12/3 & 14/3 Cable T®-Stripper Wire Stripper	45-622

NM Cable Dual-Hole T[®]-Stripper Wire Stripper

- Stripping holes for stripping two 12 AWG or two 14 AWG wires simultaneously
- Ability to strip both conductor wires of NM cable at one time

ires		
1100	10 · 10	
1 3 9 9		
anar		0
1 alesta		C.

Description	Wire Range	Cat. No.
Premium T®-14 T®-Stripper Wire Stripper	12 or 14 AWG solid	45-247

Romex® is a registered trademark of Southwire.

Super T[®]-Stripper Wire Strippers

- 6-32 and 8-32 self-chasing screwcutting holes (not available on metric stripper)
- Curved, cushion-grip handles for ergonomic comfort
- Locking pawl to keep stripper in closed position
- Built-in wire cutter and looping holes
- Convenient plier nose for extra gripping strength
- Laser-etched wire gauge for easy-to-read visibility
- Spring-loaded automatic opening
- Tough steel construction, corrosion-resistant, black oxide finish

Description	Solid	Stranded	Cat. No.
Super T [®] -5 T [®] -Stripper Wire Stripper	8-16	10-18	45-315
Super T [®] -8 T [®] -Stripper Wire Stripper	6-14	8-16	45-318
Super T [®] -Stripper Wire Stripper – Metric	0.5-4mm ²		45-310-341
Super T [®] -Stripper Wire Stripper – Metric	0.75-6mm ²		45-315-341
Super T [®] -Stripper Wire Stripper – Metric	0.5-4mm ²		45-317-341

Lil' Ripper Stripper™

- Rips Romex[®] outer jacket cleanly and quickly
- Clips outer sheathing to remove excess Romex[®] jacket
- Strips inner conduit wires
- Looping holes loop wire for screw-on connections
- Twist-Assist[™] tightens most popular sizes of winged twist-on connectors
- Injection molded elastomer grip provides a comfortable, slip resistant grip
- Strip length measuring scale allows for quick and easy measurements
- Conveniently fits in your pocket

Description	Cat. No.
Lil' Ripper Stripper™	45-025

Reflex™ Super T®-Stripper Wire Strippers

- 6/32 and 8/32 self-chasing screw-cutting holes
- Locking pawl for safe storage
- Ergonomic design for maximum comfort
- Curved handles reduce wrist fatigue
- Sleeves that extend to stripping head to cushion thumb and fingers
- Textured sleeves with extra cushioning for added comfort

Description	Solid	Stranded	Cat. No.
Reflex™ Super 12/2 & 14/2 NM Cable T®-Stripper Wire Stripper	12-2 and 14-2	—	45-621
Reflex™ Super 12/3 & 14/3 NM Cable T®-Stripper Wire Stripper	12-3 and 14-3		45-622

TES

Vire Strippers

C-4

Super T[®]-Stripper Wire Strippers-**Static Dissipative**

- Static dissipative grips for dispersing static charge buildup through the operator to the ground (operator must be grounded via wrist strap or other grounding device)
- Locking pawl to keep stripper in closed position

Description	Solid	Stranded	Cat. No.
Super T®-6 T®-Stripper Wire Stripper w/static dissipative grips	14-24	16-26	45-316
Super T [®] -7 T [®] -Stripper Wire Stripper w/static dissipative grips	22-30	24-32	45-317

V-Notch Stripper

- Cuts copper or aluminum wire, solid or stranded
- Rotating cam wheel adjusts to strip 10-24 AWG wire
- Looping holes for solid wire
- Locking hasp

0	
Description	Cat. No.
V-Notch Stripper	45-101

7-in-1 Stripper



- Versatile, seven-function tool features precision-ground stripping blades, cushioned grips and plier nose
- Strips 8 16 AWG solid and 10 18 AWG stranded wire
- Crimps bare and insulated terminals for 10 22 AWG wire, RG-59 coax connectors and 7 to 8mm auto ignition connectors
- Cuts unhardened wire, bolts and screws (4-40, 6-32, 8-32, 10-24) and 10-32) and reforms threads
- Cuts stranded, solid, Romex[®] and U.F. wire to 8 AWG
- Reams and de-burrs conduit
- Gauges and loops wire

Description	Cat. No.
7-in-1 Stripper	45-777

Romex® is a registered trademark of Southwire.

Ringer[™] Shielded Cable Stripper

Precision stripping for most non-round cable, including extruded Teflon®, Kapton®, Tefzel[®], Kynar[®] and hightemperature insulations



- Spring-loaded head provides even tension
- Heat-treated, stainless-steel blades resist wear
- Fixed blades are sized to insulation thickness, for accurate stripping
- V-notch jaw automatically positions and holds cable
- Wire guide roller maintains stripping head alignment, for square, clean cuts

Description	Blade	Color	Cat. No.
Cable Stripper, 5 Mil insulation, includes blade	K-6492	(Orange)	45-401
Cable Stripper, 8-10 Mil insulation, includes blade	K-6493	(Yellow)	45-402
Cable Stripper, Cable diameters up to 0.12 in.	sold separately	(Blue)	45-400
Cable Stripper, Cable diameters from 0.12 in. to 0.22 in.	sold separately	(Red)	45-403
Cable Stripper, w/"deep V" forcable diameters up to 0.30 in.	sold separately	(Green)	45-404

Replacement Blades

Cutting Depth	Cat. No.	Cutting Depth	Cat. No.	Cutting Depth	Cat. No.
.0030 in.	K-6491	.0100 in.	K-6497	.0180 in.	K-6503
.0044 in.	K-6492	.0110 in.	K-6498	.0200 in.	K-6504
.0060 in.	K-6493	.0120 in.	K-6499	.0220 in.	K-6505
.0070 in.	K-6494	.0130 in.	K-6500	.0250 in.	45-2108-1
.0080 in.	K-6495	.0140 in.	K-6501		
.0090 in.	K-6496	.0160 in.	K-6502		

Select blade with cutting depth less than insulation thickness.

Wire Stops



beeenphen	out non
Up to 2-1/2 in.	LB-825
2-1/2 in. to 5 in.	LB-840

IDEAL Gripper™	A45-333 Crippor* Stug Romover Maria Mar	
Description	Sylamire, 8 USA	Cat. No.
Slug Remover		45-333

Teflon® and Kapton® are registered trademarks of E.I. duPont de Nemours and Company. Kynar® is a registered trademark of Pennwall.





- Cuts round communication cable and maintains cable geometry for better cable performance
- Cuts multi-pair cable up to .500 in. (12.7mm) and coaxial cable up to RG-9/U
- Suitable for soft cables (not ACSR)
- Steel reinforced center conductors can be trimmed with bolt cutting holes
- Cushioned comfort grip handles
- Locking latch keeps tool closed in pouch
- Data T[®]-Cutter II designed for RG-58 and RG-6 coaxial cable

Description	Cat. No.
Data T [®] -Cutter	45-074
Data T [®] -Cutter II	45-075

Combo Tool

- Convenient, four-function tool features precision-ground stripping holes and knife-to-anvil cutting blades
- Crimps bare and insulated terminals
- Strips 8 20 AWG solid and 10 22 AWG stranded wire
- Cuts unhardened bolts (4-40, 6-32, 8-32, 10-24 and 10-32) and reforms threads

Description	Cat. No.
Combo Tool	30-428

Multi-Crimp Strip Tool

- Cuts wire
- Crimps insulated and non-insulated wires
- Cuts bolts
- Strips 10-22 AWG wire

Description	Cat. No.
Multi-Crimp Strip Tool	45-778

T®-Cutter Wire Cutters

- Hardened steel, sheer-type blades
- Spring-loaded automatic opening
 Convenient plier nose for extra gripping strength
- Corrosion-resistant, black oxide finish
- Tough steel construction
- Locking tab keeps spring in place

Description	Wire Range	Cat. No.
T®-Cutter Wire Cutter	Up to 1/2 in. O.D. fine-stranded wire and 10 AWG solid wire	45-123
Reflex™ Premium T®-Cutter Wire Cutter	Up to 1/2 in. O.D. fine-stranded wire and 10 AWG solid wire	45-423

T[®]-Cutter Lite Wire Cutter

In today's cutting-edge electronic production and assembly operations, the T[®]-Cutter Lite is a "must-have." Stranded or solid, copper or aluminum, this wire cutter cuts cleanly and accurately. Compact and lightweight with a cushioned ESD grip prove comfort and precision go hand-in-hand.

- Knife-type blade provides a shear-type cut
- Lightweight, compact design
- Perfect for copper and aluminum wire
- Cushioned ESD grip

Description	Cat. No.
T®-Cutter Lite Wire Cutter	45-260

Coax Strip and Crimp Tool	
Precision, form-ground stripping holes remove outer jacket and insulation from RG-59 and RG-6 coaxial cable	
Durable blades cut copper-coated steel conductors	

Three crimping nests for crimping F-connectors and ring terminals

Description	Cat. No.
Coax Strip & Crimp Tool	30-433
Coax Strip & Crimp Tool w/F-Connectors	30-433F

Cable Ripper

Slits cable sheathing before stripping wires



Convenient built-in wire gauge

Description	Cat. No.
Side Entry Cable Ripper	45-118

Underground Feeder (UF) Cable Stripper

- Self-adjusting stripping blades automatically select proper position
- Strips 12 AWG solid to 14 AWG Underground Feeder (UF) Cable
- Strips Twin and Earth cable
- Open-throat construction allows unlimited strip length
- Neatly removes outer cable sheath and then inner wire sheathing to desired lengths
- Lightweight, ergonomic design reduces user fatigue

Description	Cat. No.
Underground Feeder Cable Stripper	45-235

Grip-N-Strip[™] **End Stripper**

- Self-adjusting stripping blades automatically select proper position
- Strips 12 AWG solid to 20 AWG stranded PVC insulated wire
- Dual strip-length gauge marks at 3/16 in. and 5/16 in.
- Cuts up to 12 AWG solid wire
- Lightweight, ergonomic design reduces user fatigue
- Reinforced fiberglass construction
- Hardened steel blades for extra strength and longer life

Description	Cat. No.
Grip-N-Strip™ End Stripper	45-227

SII NICKIESS Cutter TO SEVER AND PROTECT ARMORED CABLE

- Handles all common BX, MCAP, MC and Flex cables
- Blade cuts armor without damage to internal conductors
- Splices cleanly through casings with only a few turns



Handle knob stores up to six replacement blades

Description	Cat. No.
Replacement blades (5/pack)	35-781
Rotary Armored Cable Cutter	35-782

Round Cable Slitting and Ringing Tool

- Cuts around cable jacket as well as slits the length of jacket for easy removal
- Use with single or multiple conductor cable up to 1.75 in. O.D.
- Blade adjusts for jacket thicknesses up to .125 in.
- Spare blade in handle base

Description	Cat. No.
Cable Stripper for 1/4 in. to 3/4 in. O.D.	45-128
Cable Stripper for 3/4 in. to 11/2 in. O.D.	45-129
Replacement Blades for 45-128 and 45-129 (2/pkg.)	L-7486

One-step stripping enchances productivty	
Spring-action motion increases leverage and reduces operator fatigue	annul and a
Precision-ground, knife-type blades provide clean, accurate stripping	
Description	Cat. No.
Stripmaster [®] Wire Stripper, 10-22 AWG	45-092
Stripmaster [®] Wire Stripper, Coax RG-6	45-262
Stripmaster® Wire Stripper, 10-22 AWG	45-292

See Section D for complete Stripmaster® Wire Stripper line.

Stripmaster[®] Wire Strippers















LASERedge[™] pliers use high carbon, 1080 steel, which provides extra strength and hardness without sacrificing flexibility. It is one of the reasons our tools outperform the competition in performance and durability. All of our LASERedge tools have laser-hardened blades and teeth, which are more precise and provide better durability for strenuous applications like cutting steel or ACSR.

FETIM





- Drop-forged, high-carbon steel construction withstands toughest applications
- Knife-to-anvil blades never need resharpening
- Cuts hardened wire, bolts and ACSR
- Laser-hardened blades and serrated jaws for long-term durability
- High-leverage design provides 40% more cutting power
- Unique reverse rivet protects smooth action of plier movement
- Vinyl-coated, comfort-grip handles for a secure grip

Description (Smart-Grip™ Handles)	Cat. No.
9-1/4 in. New England nose high-leverage w/fish tape puller	35-3012
9-1/4 in. New England nose high-leverage w/crimping die	30-3430
Description (Dipped Handles)	Cat. No.
9-1/4 in. New England nose high-leverage w/fish tape puller	35-012
9-1/4 in. New England nose high-leverage w/crimping die	30-430



- Mirror-polished finish to maintain premium appearance
- Double-dipped grips for extra cushioning comfort

w/fish tape puller and crimping die	30-435







- Laser-hardened blades cut hardened wire, bolts and ASCR
- Vinyl-coated, comfort-grip handles for a secure grip
- High-leverage design provides 40% more cutting power
- Models 35-029 and 35-3029 feature a convenient angled head for hard-to-reach areas and rocking out nails

Long-Nose Pliers

35-3038

8 in. High-leverage Diagonal	35-3028
8 in. High-leverage Diagonal w/angled head	35-3029
Description (Dipped Handles)	Cat. No.
8 in. High-leverage Diagonal	35-028
8 in. High-leverage Diagonal w/angled head	35-029
-	

- Narrow profile head designed for working in tight areas
- Serrated jaws provide secure gripping surface
- Drop-forged, high-carbon steel construction
- Knife-to-anvil blades never need resharpening
- Laser-hardened blades cut hardened wire, bolts and ASCR
- Vinyl-coated, comfort-grip handles for a secure grip

Description (Smart-Grip™ Handles)	Cat. No.
8-1/2 in. Long Nose w/Cutter	35-3038
Description (Dipped Handles)	Cat. No.
6 in. Long Nose w/Cutter	35-036
7-3/4 in. Long Nose w/Cutter	35-037
8-1/2 in. Long Nose w/Cutter	35-038
8-1/2 in. w/Cutter & stripping holes for 12 & 14 AWG wire	35-039

35-039

FETIA IDEAL ARAN

Tongue and Groove Pliers			•
35-3430	35-40	60	UFETIMA IDEAL CLARANTE
	Description (Smart-Grip™ Handles)	Jaw Opening (Inches)	Cat. No.
Patented undercut tongue and groove design	10 in. Tongue & Groove Pliers	2	35-3430
ensures solid gripPatented reinforced flange protects against	Description (Dipped Handles)	Jaw Opening (Inches)	Cat. No.
breakage	6-1/2 in. Tongue & Groove Pliers	7/8	35-426
Laser-hardened teeth remain sharp longer	9-1/2 in. Tongue & Groove Pliers	1-1/2	35-420
	10 in. Tongue & Groove Pliers	2	35-430
Drop-forged, high-carbon steel construction	12 in. Tongue & Groove Pliers	2-1/4	35-440
Vinyl-coated, comfort-grip handles for a secure grip	16 in. Tongue & Groove Pliers	4-1/4	35-460

C-10 www.idealindustries.com



Description (Dipped Handles)

9-3/4 in. Multi-Crimp Tool

- Knife-to-anvil blades never need resharpening
- Excellent leverage for easy crimping and cutting
- Drop-forged, high-carbon steel construction
- Vinyl-coated handles provide a solid, comfortable grip

Crimp Tool

- Crimps all IDEAL crimp sleeves
- Excellent leverage for right-angle, double-indent crimps
- Cuts and twists wire
- Vinyl-coated handles provide a solid, comfortable grip

Description	Cat. No.
Crimp Tool - 10-1/4 in.	30-425



Cat. No.

30-429





WireMan[™] pliers provide professional results for everyday use. These tools are the workhorse of electrical pliers; they are rugged yet precise, providing exceptional durability, easy cutting and a lifetime of quality use.





Side-Cutting Pliers

Custom chrome vanadium steel for durability

- High leverage pivot requires less cutting force
- Sharp, knife-to-knife blades for easy cutting
- Induction hardened teeth for long life
- Cross-hatched jaws so wires won't slip when pulling

30-4430

Ergonomic handles for comfortable, all-day use

35-5012

LIFETIMA
• IDEAL •
Ello St
ARAN

Description (Smart-Grip™ Handles)	Cat. No.
7 in. Cutting Pliers	30-4419
8 in. Side-Cutting Pliers	30-4420
9-1/4 in. Side-Cutting Pliers	35-4012
9-1/4 in. Side-Cutting Pliers w/crimp and fish tape puller	30-4430
Description (Dipped Handles)	Cat. No.
7 in. Cutting Pliers	30-5419
7 in. Cutting Pliers 8 in. Side-Cutting Pliers	30-5419 30-5420
<u>_</u>	

Diagonal-Cutting Pliers

35-4028





- Custom chrome vanadium steel for durability
- High leverage pivot requires less cutting force
- Sharp, knife-to-knife blades for easy cutting
- Induction hardened teeth for long life
- Ergonomic handles for comfortable, all-day use

Description (Smart-Grip™ Handles)	Cat. No.
6 in. Diagonal-Cutting Pliers	35-4026
8 in. Diagonal-Cutting Pliers	35-4028
8 in. Diagonal-Cutting Pliers w/angled head	35-4029
Description (Dipped Handles)	Cat. No.
6 in. Diagonal-Cutting Pliers	35-5026
8 in. Diagonal-Cutting Pliers	35-5028
8 in. Diagonal-Cutting Pliers w/angled head	35-5029







Ergonomic handles for comfortable, all-day use

6 in. Long-Nose Pliers w/Strip & Crimp	35-4035
6 in. Long-Nose Pliers	35-4036
8 in. Long-Nose Pliers	35-4038
Description (Dipped Handles)	Cat. No.
6 in. Long-Nose Pliers w/Strip & Crimp	35-5035
6 in. Long-Nose Pliers	35-5036
8 in. Long-Nose Pliers	35-5038

Tongue and Groove Pliers	and the second s	
35-4430	35-5430	STETIME DEALS
Custom chrome vanadium steel for durability	Description (Smart-Grip™ Handles)	Cat. No.

Ergonomic handles for comfortable, all-day use

Description (Smart-Grip™ Handles)	Cat. No.
10 in. Tongue & Groove Pliers	35-4430
Description (Dipped Handles)	Cat. No.
10 in. Tongue & Groove Pliers	35-5430



Multi-Crimp Tools

30-4429

35-5431

Description (Smart-Grip™ Handles)	Cat. No.
9-1/4 in. Multi-Crimp Tool	30-4429
9-1/4 in. Multi-Crimp Tool - Bare Terminals	35-4431
Description (Dipped Handles)	Cat. No.
9-1/4 in. Multi-Crimp Tool	30-5429
9-1/4 in. Multi-Crimp Tool - Bare Terminals	35-5431



35-4052

Custom chrome vanadium steel for durability

Custom chrome vanadium steel for durability High-leverage pivot requires less force

Ergonomic handles for comfortable, all-day use Cuts, crimps and splices 10 – 22 AWG wire for insulated and non-insulated crimp connectors

- High-leverage pivot requires less force
- Sharp, knife-to-knife blades for easy cutting
- Induction hardened teeth for long life
- Ergonomic handles for comfortable, all-day use



	ELARANTE
Description (Smart-Grip™ Handles)	Cat. No.
9 in. 2/0 Cable Cutter	35-4052
Description (Dipped Handles)	Cat. No.
9 in. 2/0 Cable Cutter	35-5052

Tenite Grips

- Fits LASERedge[™] and WireMan[™] Pliers
- Not insulated from electrical shock
- Boil in water to soften for easy installation onto handles



Description	Cat. No.
Replacement grips for 6 in. pliers (one pair)	35-006
Replacement grips for 7 in. pliers (one pair)	35-007
Replacement grips for 8 in. or 9 in. pliers (one pair)	35-008

SFETIM

IDEAL . ARAN







1/4 in. slotted - #2 Square Recess

3/16 in. slotted - #1 Square Recess

Torx[®] is a trademark of Camcar division of Textron. Inc.

#15 & #10 Torx®

· · · · · · · · · · · · · · · · · · ·	· ·
Description	Cat. No.
1/4 in. slotted – #2 Phillips	35-911
3/16 in. slotted – #1 Phillips	35-912
1/4 in. slotted – #2 Square Recess	35-913
3/16 in. slotted – #1 Square Recess	35-914
#15 & #10 Torx®	35-915

Torx® is a trademark of Camcar division of Textron, Inc.



35-913

35-914

35-915

Twist-a-Nut[™] Pro Electrician's **Screwdrivers**



SET/M

IDEAL

ARAN

Vapor-blasted tip prevents plate chipping Tough, chrome vanadium steel shank

Convenient Wire-Nut® Wire Connector

Wrench in end of handle

Wire-looping hole in handle

Precision ground tip provides secure fit in screw slot

Description	Cat. No.
#2 x 6 in. Robertson	30-330
1/4 in. x 4 in. Slotted	30-331
#2 x 4 in. Phillips	30-332
1/4 in. x 6 in. Slotted Cabinet Tip	30-333

6-in-1 Twist-a-Nut[™] Tapping Tool



- Forms new threads, re-forms burred threads and cleans out obstructions
- Reversible, high-carbon tap with three clearly marked thread sizes on each end
- Handle is interchangeable with 7-in-1 Screwdriver (#35-908) and Conduit Deburrer (#35-083)

Description	Cat. No.
Twist-a-Nut™ Tapping Tool includes: 6-32, 8-32 & 10-32 on one tapping side, 10-24, 12-24 & 1/4-20 on the other	35-922
Twist-a-Nut [™] Shaft assembly includes: Collar, 35-422 & 35-423	35-923

Twist-a-Nut[™] Conduit **Deburring Tools**



- Deburrs inside and outside edges of 1/2 in., 3/4 in. and 1 in. thin wall conduit
- Hooded tip tightens EMT fitting set screws without slipping
- Square tip "seats" much more quickly on fitting screws than slotted version
- Head removes and is interchangeable with IDEAL 7-in-1 Twist-a-Nut™ Screwdriver shaft (#35-908)
- Head can be used in drill or cordless screwdriver
- Universal Wire-Nut® Wire Connector Wrench in handle end eases installation of twist-on connectors
- Lifetime guarantee (excludes blades)

Description	Cat. No.
Conduit Deburring Tool, slotted tip	35-083
Conduit Deburring Tool - head only, slotted tip	35-096
Conduit Deburring Tool - #2 square tip	35-075
Conduit Deburring Tool - head only, #2 square tip	35-098
Replacement Blades (2/pack)	35-097

Twist-a-Nut[™] Conduit Wiring Kit

Includes Twist-a-Nut™ Screwdriver (35-908), Twist-a-Nut™ Deburring Head -Square Tip (35-098), Twist-a-Nut[™] Tap Tool Shaft (35-923), Three Spare Bits (1/4 in. slotted & #2 square, 3/16 in. slotted & #1 square, #10 & #15 Torx[®]), 8-Pocket Carrying Pouch (35 - 927)



- Nylon carrying pouch holds all three Twist-a-Nut[™] tools plus room for four replacement bits or taps
- Strong easy-slide metal belt clip

Description	Cat. No.
Twist-a-Nut™ Combo Pack	35-926
Twist-a-Nut™ Carrying Pouch only	35-927

Accu-Loop[™] wire

looping holes

35-098







Cushioned-Grip Screwdrivers







- Larger shank for heavy-duty applications
- Identification mark on ends
- Vapor-blasted tip prevents plate chipping
- Precision ground tip provides secure fit in screw slot
- Square-shank models offer wrench-assisted turning
- Tough, chrome vanadium steel shank
- Cushioned rubber grips

Square Shank	Blade Length	Total Length	Cat. No.
1/4 in. Shank and tip	4 in.	8-3/8 in.	35-154
5/16 in. Shank and tip	6 in.	11 in.	35-156
5/16 in. Shank and tip	8 in.	13 in.	35-158

Round Shank	Blade Length	Total Length	Cat. No.
1/4 in. Shank and tip	1 in.	3-3/8 in.	35-161
1/4 in. Shank and tip	4 in.	8-3/8 in.	35-164
5/16 in. Shank and tip	6 in.	11 in.	35-166
5/16 in. Shank and tip	8 in.	13 in.	35-168

Slotted Heavy-Duty w/Cabinet Tip



- Large diameter shank for tough applications
- Identification marks on ends
- Vapor-blasted tip prevents plate chipping
- Precision ground tip provides secure fit in screw slot
- Nickel-chrome plating for corrosion resistance
- Tough, chrome vanadium steel shanks
- Cushioned rubber grip

Description	Blade Length	Total Length	Cat. No.
1/4 in. Shank and tip	4 in.	8-3/8 in.	35-150
1/4 in. Shank and tip	6 in.	10-3/8 in.	35-151
1/4 in. Shank and tip	8 in.	12-3/8 in.	35-152
1/4 in. Shank and tip	10 in.	14-3/8 in.	35-153





- Vapor-blasted tip prevents plate chipping
- Identification mark on ends
- Precision ground tip provides secure fit in screw slot
- Nickel-chrome plating for corrosion resistance
- Tough, chrome vanadium steel shank
- Cushioned rubber grip

Description	Blade Length	Total Length	Cat. No.
3/16 in. Shank and tip	3 in.	6-3/4 in.	35-183
3/16 in. Shank and tip	4 in.	7-3/4 in.	35-184
3/16 in. Shank and tip	6 in.	9-3/4 in.	35-186
3/16 in. Shank and tip	8 in.	11-3/4 in.	35-188
3/16 in. Shank and tip	10 in.	13-3/4 in.	35-190



- Vapor-blasted tip prevents plate chipping
- Identification mark on ends
- Nickel-chrome plating for corrosion resistance
- Tough, chrome vanadium steel shank
- Cushioned rubber grip

Description	Blade Length	Total Length	Cat. No.
#1 Phillips	3 in.	6-3/4 in.	35-193
#2 Phillips	1 in.	3-3/8 in.	35-191
#2 Phillips	4 in.	8-3/8 in.	35-194
#2 Phillips	6 in.	10-3/8 in.	35-195
#3 Phillips	6 in.	11 in.	35-196







- Ideal for threading screws in switches, fixtures and anchors
- Identification mark on ends
- One-handed crank action for quick and easy use
- Vapor-blasted tip prevents plate chipping
- Precision-ground tip provides secure fit in screw slot
- Nickel-chrome plating for corrosion resistance
- Tough, chrome vanadium steel shank
- Cushioned rubber grip

Description	Total Length	Cat. No.
3/16 in. Shank and Tip	8-3/4 in.	35-200
#2 Phillips Tip and 1/4 in. Shank	9-3/4 in.	35-203





- Precise tip for square-recess screws
- Color-coded handle for easy identification
- Nickel-chrome plating for corrosion resistance
- Tough, chrome vanadium steel shank
- Cushioned rubber grip

Description	For Screw Sizes	Cat. No.
#0 x 4 in.	3, 4	35-690
#1 x 4 in.	5, 6, 7	35-691
#1 x 8 in.	5, 6, 7	35-692
#2 x 4 in.	8, 9, 10	35-693
#2 x 8 in.	8, 9, 10	35-694
#3 x 4 in.	12, 14	35-695
#3 x 8 in.	12, 14	35-696



- Heavy-duty construction for piercing, punching and scribing
- Identification mark on end
- Cushioned rubber grip

Description	Blade Length	Total Length	Cat. No.
Awl	3 in.	6-3/4 in.	35-202

Screw-Holding

- Holds screw when collar is extended
- Holds screw in place when installing in hard-to-reach locations
- Tough, chrome vanadium steel shank and comfort grip handle

Description	Blade Length	Total Length	Cat. No.
3/16 in. Slotted	6 in.	10 in.	35-406
#2 Phillips	7 in.	11 in.	35-404

Nutmaster® Nutdrivers



- Long, hollow shank handles longer bolts
- Identification and color coding on ends
- Nickel/chrome plated to resist rust and corrosion
- Cushioned rubber grips
- Models 35-292 and 35-295 fit Twister[®] Wire Connectors



Description	Shaft Length	Color	Cat. No.
3/16 in.	3-1/4 in.	Black	35-290
1/4 in.	3-1/4 in.	Red	35-291
5/16 in.	3-1/4 in.	Yellow	35-292
11/32 in.	3-1/4 in.	Green	35-293
3/8 in.	3-1/4 in.	Blue	35-294
7/16 in.	4 in.	Brown	35-295
1/2 in.	4 in.	Red	35-296



- Phosphate tip for longer wear life
- Rotating cap for optimum control for precise centering
- Color-coded cap for easy identification

Description	Style	Blade Length	Cat. No.
3/32 in.	Cabinet Tip	2-1/2 in.	36-240
3/32 in.	Cabinet Tip	3 in.	36-241
1/8 in.	Cabinet Tip	4 in.	36-242
1/8 in.	Cabinet Tip	6 in.	36-243
5/32 in.	Cabinet Tip	4 in.	36-244
5/32 in.	Cabinet Tip	6 in.	36-245
#0 — 1/8 in.	Phillips Head	2-1/2 in.	36-246
7-Piece Set includes one eac	h of 36-240 thru 36	-246	36-248
4-Piece Set includes one eac	h of 36-240, -241,	-242 & -246	36-249

7-Piece Nutdriver Set



10-in-1 Screwdriver/Nutdriver

Includes 1/4 in. slotted, #2 Phillips, 3/16 in. slotted, #1 Phillips, #1 & #2 square recess, #15 and #10 Torx[®] and 5/16 in. & 1/4 in. Nutdriver

Cushion grip for comfort and

- performance Description Cat. No. 10-in-1 Screwdriver/Nutdriver 35-910 **Replacement Bits (for 10-in-1 Screwdriver)** Description Cat. No. 1/4 in. slotted - #2 Phillips (2/pack) 35-940 3/16 in. slotted - #1 Phillips (2/pack) 35-941 35-942 #1 & #2 Square Recess (2/pack) #15 & #10 Torx® (2/pack) 35-943

Torx[®] is a trademark of Camcar division of Textron, Inc.



Replacement Bits (for 5-in-1 Screwdriver)

Description	Cat. No.
#1 Phillips – 3/16 in. slotted	LA-4123
#2 Phillips – 9/32 in. slotted	LA-4124

Recessed Light Kit

- All the tools needed to install recessed lights
- Long spring tool easily installs and removes spring
- Compact nutdriver is 2-1/4 in. providing added clearance in recess lighting
- Cushion grip for added comfort

Description	Cat. No.
Recessed Light Kit	35-698





PowerBlade™ Cable Cutter



- Extremely versatile: fits almost any drill (12V minimum)
- Cuts up to 750 MCM hard drawn copper, 1000 MCM aluminum*
- Heavy-duty gears and specially hardened blades for professional quality
- Rounded blade design minimizes cable distortion during cutting
- No need to mess with battery packs or special chargers; this tool works with the drill you already carry!

(Folding handle for storage.)

35-033

Description	Cat. No.
PowerBlade™ Cable Cutter	35-078
PowerBlade [™] Replacement Handle	K-8947R
PowerBlade [™] Replacement Blades (pair)	K-8906R
PowerBlade [™] Replacement Torque Arm Assembly	K-8909
PowerBlade™ Replacement Carrying Case	K-8926

*Max. Jaw Opening - 2 in. Not for cutting steel or ASCR.

Long-Arm Cable Cutters

- High strength forged blades for ultimate durability
- Precision-ground jaws make clean cuts with minimal cable distortion
- Replaceable blades
- For copper and aluminum only. Not designed for steel or ACSR.

Description	Length	Cat. No.
250 MCM Long-Arm Cable Cutter	14 in.	35-031
500 MCM Long-Arm Cable Cutter	22 in.	35-032
1000 MCM Long-Arm Cable Cutter	32 in.	35-033
Replacement Head – 250 MCM (for 35-031)		35-031B
Replacement Head – 500 MCM (for 35-032)		35-032B
Replacement Head – 1000 MCM (for 35-033)		35-033B

CAUTION: Comfort-grip handles are not designed for protection against electrical shock. Do not use on live circuits.

Ratcheting Cable Cutter

- Cuts hard drawn copper up to 400 KCMIL (MCM) and soft copper, aluminum and multiple conductor cable up to 600 KCMIL (MCM)
- Hardened steel blades ensure consistent cuts and long-term durability
- Rounded blade design minimizes cable distortion during cutting
- Quick release mechanism simplifies blade back-out
- Locking mechanism keeps handles closed for easy storage

Description	Cat. No.
400 KCMIL (MCM) Ratcheting Cable Cutter*	35-056
Replacement blade (moveable side only)	35-085

*Max. Jaw Opening - 1.375 in. Not for cutting steel or ASCR.

Ratcheting Cable Cutter

- 750 KCMIL Ratcheting Cable Cutter is designed to cut 750 KCMIL (MCM) and smaller hard-drawn copper and aluminum cables
- Hardened steel blades ensure consistent cuts and long-term durability
- Rounded blade design minimizes cable distortion during cutting
- Quick release mechanism simplifies blade back-out
- Locking mechanism keeps handles closed for easy storage
- Molded-in foot provides stability and leverage when making multiple cuts

Description	Cat. No.
750 KCMIL (MCM) Ratcheting Cable Cutter*	35-053
Replacement blade (moveable side only)	35-057

*Max. Jaw Opening - 2 in. Not for cutting steel or ASCR.

Telco Ratcheting Cable Cutters

- Telco Ratcheting Cable Cutter jaw cuts up to 2,700 pair telephone cable and Stalpath[®] type communications cable
- Hardened steel blades ensure consistent cuts and long-term durability
- Rounded blade design minimizes cable distortion during cutting
- Quick release mechanism simplifies blade back-out
- Locking mechanism keeps handles closed for easy storage
- Molded-in foot provides stability and leverage when making multiple cuts

Description	Cat. No.
Telco Ratcheting Cable Cutter*	35-055
Replacement blade (moveable side only)	35-054

*Max. Jaw Opening - 3 in. Not for cutting steel or ASCR.







- Handles all common BX, MCAP, MC and Flex cables
- Blade cuts armor without damage to internal conductors
- Splices cleanly through casings with only a few turns
- Handle knob stores up to six replacement blades

Description	Cat. No.
Replacement blades (5/pack)	35-781
Rotary Armored Cable Cutter	35-782

Mechanical Indentor and Crimp Tool



- Use with aluminum (6 AWG to 4/0) and copper (8 AWG to 250 KCMIL) wires
- Adjustable crimping nests with clearly marked gauges
- Lightweight and easy to operate
- Rugged cast steel construction for long-term durability
- Connections are UL Listed when using this tool with IDEAL Non-Insulated Terminals (#8 - #4 AWG).

Description	Cat. No.
Mechanical Indentor	88-843

Heavy-Duty Crimp Tool

- Crimp nests for 2, 4, 6 or 8 AWG and 8-38 mm² uninsulated terminals
- Rotating crimp nests eliminate costly die changes
- Decimal and metric wire sizes clearly marked on each crimp nest
- Comfort-grip handles for a secure grip
- Connections are UL Listed when using this tool with IDEAL Non-Insulated Terminals (#8 - #4 AWG).

Description Heavy-Duty Crimp Tool

Crimp Tool

- Crimps all IDEAL crimp sleeves
- Excellent leverage for rightangle, double-indent crimps
- Cuts and twists wire
- Vinyl-coated handles provide a solid, comfortable grip

Description	Cat. No.
Crimp Tool - 10-1/4 in.	30-425

Buchanan Construction Products Four-Way Crimp Tool

- Patented design ensures even compression and reliable connections
- Spring-loaded, camactuated plungers
- Fingertip adjustment for different connector sizes

Description	Cat. No.
Four-Way Crimp Tool	C-24

Ratchet Crimp Tool

- Crimps insulated or bare terminals and splices on 10 - 22 AWG wire
- Ratchet action prevents release prior to crimp connection helps ensure uniform crimps
- Vinyl-coated handles provide a solid, comfortable grip

Description	Cat. No.
Ratchet Crimp Tool	83-001

Cat. No.

83-005

SETIA

IDEA







- Narrow profile head reaches into tight spaces
- Tight tolerance on thumbscrew won't loosen or wobble with use
- Extra wide jaw capacity with standard and metric markings
- Lightweight, non-conductive handle (not insulated)

Description	Jaw Capacity	Cat. No.
8 in. Adjustable Wrench	1-1/8 in.	35-020
10 in. Adjustable Wrench	1-5/16 in.	35-021

6-in-1 Twist-a-Nut[™] **Tapping Tools**



- tap with three clearly marked thread sizes on each end
- Handle is interchangeable with 7-in-1 Screwdriver (#35-908) and Conduit Deburrer (#35-083)

Description	Cat. No.
6-in-1 Twist-a-Nut™ Tap Tool (includes 6-32, 8-32 & 10-32. 10-24, 12-24 & 1/4-20 taps)	35-923

Triple-Tap Tool

- Cleans and chases burred threads
- Taps three hole sizes

Description	Cat. No.
Triple Tap Tool (includes 10/24, 8/32, & 6/32 taps)	35-411
Triple Tap Tool (includes 10/32, 8/32, & 6/32 taps)	35-412

Replacement Taps (for 35-923, 35-411 and 35-412)

Thread Sizes	Replacement Tap Cat. No.
10/24, 8/32, & 6/32	35-421
10/32, 8/32, & 6/32	35-422
10/24, 12/24 & 1/4-20	35-423
6-32, 8-32 & 10-32 on one side, 10-24, 12-24 & 1/4-20 on the other side	35-922

IDEAL Wipes™ The Multi-Purpose Towel Pre-moistened wipes require no water Cleans dirt, grease, lube and grime Durable fabric scrubs without tearing Infused with natural hand moisturizers and Vitamin E Orange citrus scent

Description	Qty.	Cat. No.	
IDEAL Wipes™, 12 in. x 9 in.	82/can	38-500	

Forged-Steel Handled Hammer

FETIA IDEAL One-piece drop-forged, tempered-steel polished



- head and handle
- Long, straight claws simplify removal of electrical fixtures
- Comfortable, perforated anti-vibe grips
- Elongated neck for hitting inside boxes

Description	Cat. No.	
18 oz. x 12-1/2 in. Electrician's Fiberglass-handled Hammer	35-210	

Electric Engraving Tools

- Low-cost, industrial-quality marker quickly and easily engraves metal, glass, stone, ceramics, plastics, hard rubber, wood and many other hard materials
- Unique design reduces bouncing and provides smooth, easy writing
- Operates at 7,200 strokes per minute
- Stroke adjusts to vary depth of mark
- Includes carbide-tipped point for normal markings
- Diamond point available for engraving extra-hard materials (50 to 64 Rockwell, scale C)

Description	Cat. No.
Engraver w/carbide-tipped point — 120V, 60 Hz	11-111
Engraver w/carbide-tipped point & 3-conductor grounded cord & plug — 120V, 60 Hz	11-113
Carbide-tipped replacement point	11-200
Diamond replacement point	11-201





Automatic Blade Lock Measuring Tape

- Blade automatically stays out when extended
- Push button for smooth blade retraction
- Comfortable, shock-resistant rubber grip

Description	Cat. No.
Auto-Lock™ Tape Measure - 25 ft.	35-242

Magnetic-Tip Measuring Tape

- Strong magnetic tip for one person measurement
- Durable nylon coated blade
- Full rubber jacket protects case

Cat. No.

35-238

Des	cripti	on		

|--|

Torpedo Level



- 9 in. aluminum frame with magnetic and V-grooved edges
- White windows provide easy reading of plumb level and 45° mitre in dim lighting

Description	Cat. No.
9 in. Torpedo Level	35-205

Hex-Key Sets

- 8650 steel construction
- Dual-durometer, slip-resistant grip



Description	Cat. No.
4 in. handle w/nine 3-in. keys (5/64 in., 3/32 in., 7/64 in., 1/8 in., 9/64 in., 5/32 in., 3/16 in., 7/32 in. & 1/4 in.)	35-146
5-1/4 in. handle w/five 5-in. keys (3/16 in., 7/32 in., 1/4 in., 5/16 in. & 3/8 in.)	35-147

Utility Knife

- Quick-change retractable blade system - no disassembly required
- Built in pull-line cutter
- Includes three blades in storage compartment

Description	Cat. No.
Utility Knife	35-300
Replacement blades – Universal (10/pack)	35-301

Pocket Knives



- 2-1/4 in. blade locks in position
- High-carbon stainless steel blade construction for extra strength and durability
- Durable Buyrate[®] non-slip handle
- Brass liners

Description	Cat. No.
Electrician's Knife w/spearpoint and screwdriver blade	35-285
Hawkbill Knife w/curved blade	35-286
Lineman's Jack Knife w/sheepfoot blade	35-287





Tool Kits featuring

17-Piece Set -#35-809



Set Includes:

- Four LASERedge™ Pliers with Smart-Grip™ Handles (#35-3012 9-1/4" Linesman w/fish tape puller, #35-3038 - 8" Long Nose, #35-3430 - 10" Tongue and Groove, #35-3052 - 9-1/2" Cable Cutter)
- #45-915 Kinetic™ Reflex™ T®-Stripper Wire Stripper
- #35-908 7-in-1 Twist-A-Nut™ Screwdriver
- #Five Cushion Grip Screwdrivers (#35-193 #1 x 3 Phillips, #35-194 #2 x 4 Phillips, #35-186 – 3/16" x 6 Slotted Cabinet Tip, #35-164 – 1/4" x 4 Slotted round shank, #35-406 – 3/16" x 6 Screw holding slotted)
- #35-286 Hawkbill Knife
- #35-210 Electrician's Hammer
- #35-242 25' Auto-Lock™ Tape Measure
- #35-205 Torpedo Level
- #61-086 Vol-Con® XL Voltage/Continuity Tester
- #35-975 Tuff-Tote™ Premium Leather Tool Carrier

13-Piece Set -#35-790



Set Includes:

- Three LASERedge[™] Pliers with Smart-Grip[™] handles (#35-3012 9-1/4" Linesman w/fish tape puller, #35-3038 - 8" Long Nose, #35-3430 - 10" Tongue and Groove)
- #45-915 Kinetic™ Reflex™ T®-Stripper Wire Stripper
- Four Cushion Grip Screwdrivers (#35-193 #1 x 3 Phillips, #35-194 -#2 x 4 Phillips, #35-186 - 3/16" x 4 Slotted Cabinet Tip, #35-164 -1/4" x 4 Slotted round shank)
- #35-242 25' Auto-Lock™ Tape Measure
- #35-286 Hawkbill Knife
- #34-002 Medium Size Fuse Puller
- #35-205 Torpedo Level
- #35-462 Journeyman Electrician's Tote™

16-Piece Set -





Set Includes:

- Five LASERedge Pliers with dipped grips (#30-430 9-1/4" Linesman w/ crimper, #35-029 – 8" Offset Diagonal, #35-038 – 8" Long Nose, #35-430 – 10" Tongue and Groove, #35-052 – 2/0 Cable Cutter)
- #45-120 Premium T®-5 T®-Stripper Wire Stripper
- #35-908 7-in-1 Twist-A-Nut™ Screwdriver
- Two Cushion Grip Screwdrivers (#35-194 #2 x 4 Phillips, #35-164 1/4 x 4 Slotted round shank)
- #35-083 Twist-A-Nut™ Conduit Deburring Tool
- #35-210 Electrician's Hammer
- #35-242 25' Auto-Lock™ Tape Measure
- #35-285 Electrician's Knife
- #61-086 Vol-Con® XL Voltage/Continuity Tester
- #61-201 Replacement battery
- #35-311 Tuff-Tote™ Leather Tool Pouch

16-Piece Set -#35-808



Set Includes:

- Four LASERedge Pliers with dipped grips (#35-012 9-1/4" Linesman w/fish tape puller, #35-038 8" Long Nose, #35-430 10" Tongue and Groove, #35-012 9-1/2" Cable Cutter)
- #45-415 Reflex™ T®-5 T®-Stripper Wire Stripper
- #30-428 Combo Crimp/Strip Tool
- Four Cushion Grip Screwdrivers (#35-193 #1 x 3 Phillips, #35-194 #2 x 4 Phillips, #35-186 – 3/16" x 6 Slotted Cabinet Tip, #35-164 – 1/4" x 4 Slotted round shank)
- #35-210 Electrician's Hammer
- #35-242 25' Auto-Lock™ Tape Measure
- #34-002 Pocket Fuse Puller
- #35-286 Hawkbill knife
- #35-261 Ergonomic Hacksaw
- #35-427 18" Large Mouth Bag

Tool Kits featuring **Pliers**

12-Piece Set -#35-805



Set Includes:

- Four LASERedge[™] Pliers with dipped grip handles (#35-012 9-1/4" Linesman w/fish tape puller, #35-028 – 8" Diagonal, #35-038 – 8" Long Nose, #35-430 – 10" Tongue and Groove)
- #45-120 Premium T[®]-5 T[®]-Stripper Wire Stripper
- Four Cushion Grip Screwdrivers (#35-193 #1 x 3 Phillips, #35-194 -#2 x 4 Phillips, #35-186 - 3/16" x 4 Slotted Cabinet Tip, #35-164 -1/4" x 4 Heavy-Duty Slotted round shank)
- #35-242 25' Auto-Lock™ Tape Measure
- #10-466 Electrician's Leather Tool Pouch
- #10-398 Web Belt



6-Piece Set -

#35-794

Set Includes:

• #35-242 - 25' Auto-Lock™ Tape Measure

• One LASERedge Plier with dipped grip handles

(#30-430 - 9-1/4" Linesman w/crimper)

- #35-300 Utility Knife
- #35-505 Pocket Pal[™] Tool Holster
- **Tool Kits** featuring Pliers

12-Piece Set -#35-5805



Set Includes:

- Four WireMan[™] Pliers with dipped grip handles (#35-5012 9-1/4" Linesman, #35-5028 - 8" Diagonal, #35-5038 - 8" Long Nose, #35-5430 - 10" Tongue and Groove)
- #45-120 Premium T[®]-5 T[®]-Stripper Wire Stripper
- Four Cushion Grip Screwdrivers (#35-193 #1 x 3 Phillips, #35-194 -#2 x 4 Phillips, #35-184 - 3/16" x 4 Slotted Cabinet Tip, #35-164 -1/4" x 4 Slotted round shank)
- #25' Auto-Lock™ Tape Measure
- #10-466 Electrician's Leather Tool Pouch
- #10-398 Web Belt

5-Piece Set -35-5792



Set Includes:

- One WireMan[™] Plier with dipped grip handles (#30-5430 -9-1/4" Linesman w/crimper)
- #45-120 T[®]-5 T[®]-Stripper Wire Stripper
- Two Screwdrivers (#35-194 #2 x 4 Phillips, #35-186 3/16" x 4 Slotted Cabinet Tip)
- #35-505 Pocket Pal™ Tool Holster





Premium Leather Line

Top of the line tool carriers are handcrafted from heavy, top-grain cowhide and slow tanned in natural oils to enhance the leather's inherent strength. Each bag is hand waxed for lasting protection against stains and moisture and is warranted for life. Natural or black leather - your choice.



Standard Leather Line

Leather that stands up to the job like no other material, these tool carriers are constructed of top-grain, natural cowhide and tanned for added strength and durability. Watch their color age to a deep tan over the years.

Fabric Line

Durable, lightweight, portable tool totes in rugged nylon polyester or heavyweight canvas provide the perfect tool storage. Convenient pockets mean easy access; inner compartments keep your tools organized and safe when not in use.

Tuff-Tote[™] Ultimate Tool Carriers



- Eight-inch square tool carrier features two divided inside compartments with six screwdriver loops each, one large center compartment, four outside pockets and eight outside tool loops
- Exclusive leather-wrapped grab handle for carrying comfort
- Removable shoulder strap helps relieve lower back strain
- Unique stand-alone design keeps tools standing upright for easy identification and access
- Rust-resistant, plated-steel hardware and heavy, lock-stitched nylon thread for long-term durability
- Oil and moisture-resistant reinforced bottom

Description	Cat. No.
Premium Leather Carrier w/shoulder strap	35-975
Premium Black Leather Carrier w/shoulder strap	35-975BLK
Standard Leather Carrier w/shoulder strap	35-325

Tuff-Tote™ Tool Carriers



- Convenient 6 in. x 8 in. tool carrier with four center screwdriver slots, two interior compartments, two divided outside pockets and four outside tool loops
- Exclusive leather grab handle for carrying comfort
- Removable shoulder strap helps relieve lower back strain
- Unique stand-alone design keeps tools standing upright for easy identification and access
- Rust-resistant, plated-steel hardware and heavy, lock-stitched nylon thread for long-term durability
- Oil and moisture-resistant reinforced bottom

Description	Cat. No.
Premium Leather Carrier w/shoulder strap	35-969
Premium Black Leather Carrier w/shoulder strap	35-969BLK

Tuff-Tote[™] Tool Pouches



- Eight-pocket, belt-mounted pouch features large utility compartment with two dividers and six screwdriver loops, seven outside pockets, release snaps and tape chain
- Exclusive leather grab handle for carrying comfort
- Removable shoulder strap helps relieve lower back strain
- Rust-resistant, plated-steel hardware and heavy, lock-stitched nylon thread for long-term durability
- Tunnel belt loop accommodates belts up to 2-1/4 in. wide

Description	Cat. No.
Premium Leather Pouch w/shoulder strap	35-950
Premium Black Leather Pouch w/shoulder strap	35-950BLK





C-28 www.idealindustries.com



Description	Cat. No.
Premium Leather Pouch w/belt strap	35-956
Premium Black Leather Pouch w/belt strap	35-956BLK
Standard Leather Pouch w/belt strap	35-339

Hammer Holder

- Heavy-duty leather construction
- Riveted steel hammer loop
- Fits on all sizes of tool belts

Description	Cat. No.
Hammer Holder	10-399

Shoulder Straps



- Nickel-plated hardware for long-term durability and corrosion resistance
- 2-in. wide shoulder pad for added comfort

Description	Cat. No.
Premium Leather Strap	35-965
Premium Black Leather Strap	35-965BLK
Standard Leather Strap	35-338



Nickel-plated hardware for long-term durability and corrosion resistance

Description	Cat. No.
Premium Leather Belt – 2 in. x 48 in.	35-995
Premium Black Leather Belt – 2 in. x 48 in.	35-995BLK
Standard Leather Belt – 1-3/4 in. x 46 in.	35-316
Web Belt	10-398



Pocket Pal[™] Tool Holster

- Protects pocket from sharp tools
- Doubles tool carrying capacity
- Can be worn in pocket or on belt



Description	Cat. No.
Pocket Pal™ Tool Holster	35-505
Note: Tools sold separately.	

Belt Bag[™] Supplies Pouch

Holds wire connectors, staples, and other supplies ready for use on the job



Easy access opening closes automatically to keep supplies safely retained until needed

Description	Cat. No.
Belt Bag™ Supplies Pouch	35-405

Designed to provide perfect small parts storage - keeps parts separate and organized Six internally divided 5-in. deep pockets Convenient drawstring protects contents from spillage Convenient handle loop Sized to stack in 5-gallon buckets Durable nylon polyester construction

Divider Pouch™ Small Parts Bag

Description	Cat. No.
Divider Pouch™ Small Parts Bag	35-655
Note: Wire Connectors sold separately.	

Bucket Bag Tool Carrier

- 11-1/2 in. deep bag fits over the rim of a standard 5-gallon bucket
- Forty-three convenient pockets - 36 pleated outside and inside pockets
- Rugged nylon polyester construction



Description	Cat. No.
Bucket Bag Tool Carrier	35-665
Note: Tools sold separately.	

Supplies Apron



- Two pockets for connectors and fasteners, each 8 in. x 15 in.
- Natural duck construction

Description	Cat. No.
Supplies Apron	35-474

Zipper Pouches



- Durable, water resistant material
- Heavy duty, self-repairing zippers

Description	Cat. No.
Zipper Pouch, 10-1/2 in. long	35-402
Zipper Pouch, 12-1/2 in. long	35-403





- Top opens completely for easy access to large tools reinforced to hold itself open
- Measures 9 in. wide x 12 in. deep with outside and inside pockets for convenient hand tool storage
- Rugged zipper closure helps prevent tool loss
- Removable shoulder strap
- Durable multi-ply construction

Description	Cat. No.
Large Mouth Bag – 13 in. long	35-410
Large Mouth Bag – 16 in. long	35-418
Large Mouth Bag – 18 in. long	35-427

Note: Tools sold separately.

Journeyman Electrician's Tote™

- Compact and versatile design
- Carry as a hand-tote, shoulder-tote or tool-belt
 Includes removable shoulder strap and belt
 Durable multi-ply construction

Description	Cat. No.
Journeyman Electrician's Tote™	35-462

Master Electrician's Tote™

- Spacious and durable design
- Organizes and displays tools for fast access
- Includes removable shoulder strap
- Durable multi-ply construction

Description	Cat. No.
Master Electrician's Tote™	35-441

Mechanic's Tool Bag



- Eight narrow inside pockets designed to hold small tools
- Two side pockets with closeable snaps for large tools or loose items
- Double inside liner and rigid bottom prevent bag distortion
- Durable nylon polyester construction

Description	Cat. No.
Mechanic's Tool Bag	35-535

DEAL

Note: Tools sold separately.



Insulated Tools

The IDEAL insulated tool line creates a perfect blend of safety, comfort and precision functionality. Each tool features double insulated Santoprene[®] handles with a soft, easy-to-grip outer surface. In addition to the ergonomic qualities found in our tools, the insulated coating process acts as an 'at-a-glance' safety check. If the orange outer coating reveals any of the inner yellow surface, an electrician will know that this tool needs to be replaced.

Tools feature:

- First UL tested and classified insulated pliers
- Each one designed and tested to meet ASTM F1505-01, EN DIN, and IEC 60 900 test standards
- Individually tested and VDE certified to 1000V AC (1500V DC)
- Meets OSHA requirements for insulated tools



Warning Whenever possible, always de-energize lines and equipment prior to working on or around them. 1000V insulated tools are designed only to reduce the chance of injury where the tool may make contact with an energized source. Work around energized circuits should only be done when absolutely necessary and only by qualified technicians. <u>Property damage, personal</u> injury or death may result if the following warnings are not heeded:

- Do not use any insulated tool if the insulation cracks, breaks or becomes damaged in any way. Destroy all dual-layer tools if the inner yellow layer shows through the orange outer layer.
- Do not touch the uninsulated portion of an insulated tool or any conductive object when either might contact an energized source.
- Tools must be kept clean and dry for proper insulating properties.
- Always inspect insulated tools before use.
- Use additional protection by wearing protective clothing and approved eye protection.
- · Always use tools that are specifically designed for the task.
- These tools meet UL 22PP, ASTM F1505-01 and IEC 60900 standards for insulated tools.
- Always follow OSHA 1910 S and NFPA 70E safety requirements when doing electrical work.

REGULATIONS Testing:

 Every 1000V insulated tool we sell is individually tested to ensure no failure when subjected to live current.

UL and VDE Certification:

- Listed below are some of the tests we perform in order to pass certification:
 - Tools are immersed in water for 24 hours, then tested under current for 3 minutes to ensure no current leakage or sparkover occurs.
 - After being stored for 168 hours at -40° C (-40° F), tools are dropped to ensure no damage from impact.
 - After being stored for 168 hours at +70° C (158° F), a tensile load is applied to ensure the grip is firmly bonded to the tool.
 - Tools are subjected to flame for 10 seconds to ensure no flammability of the insulating material.

OSHA Regulations:

OSHA 1910.335(a)(2)(i) When working near exposed energized conductors or circuit parts, **each employee shall use insulated tools** or handling equipment if the tools or handling equipment might make contact with such conductors or parts.

OSHA 1910.335 (a)(1)(i) Employees working in areas where there are potential electrical hazards **shall be provided with, and shall use,** electrical protective equipment that is appropriate for the specific parts of the body to be protected and for the work to be performed.

Make sure you are in compliance by providing and using IDEAL insulated tools!

26-Piece Journeyman Kit - #35-9302



Kit Includes:

- Four insulated pliers (#30-9430 9-1/4 in. Linesman w/crimper, #35-9029 8 in. Offset diagonal, #35-9038 – 8-1/2 in. Long Nose, #35-9430 – 10 in. Tongue and Grove)
- Eight insulated screwdrivers (#35-9321 1/8 x 4 in. slotted, 3/16 x 5 in. slotted, #35-9323 1/4 x 6 in. slotted, #35-9324 5/16 x 7 in. slotted, #35-9325 3/8 x 8 in. slotted, #35-9310 #1 x 3 Phillips, #35-9311 #2 x 4 in. Phillips, #35-9312 #3 x 6 in. Phillips)
- Six insulated nutdrivers (#35-9330 3/16 x 5 in., #35-9331 1/4 x 5 in., #35-9332 - 5/16 x 5 in., #35-9333 - 3/8 x 5 in., #35-9334 - 7/16 x 5 in., #35-9335 - 1/2 x 5 in.)
- #35-9052 9-1/2 in. insulated High-Leverage Cable Cutter
- #30-9429 9-3/4 in. insulated Multi-Crimp Tool
- #45-9615 Insulated Reflex™ Super T®-Stripper Wire Stripper
- #45-9120 Insulated Wire Stripper Cutter
- #35-9340 Insulated Electrician's Skinning Knife
- #61-063 Volt-Sensor® NCV Tester
- #34-002 7-1/2 in. Non-Conductive Fuse Puller
- #35-9352 -- Heavy-Duty Soft Tool Case



18-Piece Standard Kit - #35-9301



Kit Includes:

- Four insulated pliers (#30-9430 9-1/4 in. Linesman w/crimper, #35-9029 8 in. Offset diagonal, #35-9038 – 8-1/2 in. Long Nose, #35-9430 – 10 in. Tongue and Grove)
- Eight insulated screwdrivers (#35-9320 1/8 x 4 in. slotted, #35-9321 3/16 x 5 in. slotted, #35-9323 1/4 x 6 in. slotted, #35-9324 5/16 x 7 in. slotted, #35-9325 3/8 x 8 in. slotted, #35-9310 #1 x 3 Phillips, #35-9311 #2 x 4 in. Phillips, #35-9312 #3 x 6 in. Phillips)
- #35-9052 9-1/2 in. Insulated High-Leverage Cable Cutter
- #45-9615 Insulated Reflex™ Super T[®]-Stripper Wire Stripper
- #35-9340 Insulated Electrician's Skinning Knife
- #61-063 Volt-Sensor® NCV Tester
- #34-002 7-1/2 in. Non-Conductive Fuse Puller
- #35-9351 Heavy-Duty Soft Tool Case



10-Piece Basic Kit - #35-9300



Kit Includes:

- Three insulated pliers (#34-9430 9-1/4 in. Linesman w/crimper, #35-9029 8 in. Offset diagonal, #35-9038 – 8-1/2 in. Long Nose)
- Three insulated screwdrivers (#35-9321 3/16 x 5 in. slotted, #35-9323 1/4 x 6 in., #35-9311 #2 x 4 in. Phillips)
- #35-9052 9-1/2 in. Insulated High-Leverage Cable Cutter
- #45-9615 Insulated Reflex™ Super T[®]-Stripper Wire Stripper
- #34-002 7-1/2 in. Non-Conductive Fuse Puller
- #35-9350 Heavy-Duty Soft Tool Case



Insulated Hand



Insulated Pliers



Fig.	Description	Cat. No.
А	Premium T®-Stripper Wire Stripper	45-9120
В	8 in. Diagonal Cutting Pliers w/angled head	35-9029
С	9-1/2 in. High-Leverage Cable Cutter	35-9052
D	9-1/4 in. Side Cutting Linesman Pliers	30-9430

114.20

Fig.	Description	Cat. No.
E	10 in. Tongue and Groove Pliers	35-9430
F	9-3/4 in. Multi-Crimp Tool	30-9429
G	8-1/2 in. Long-Nose Pliers	35-9038
Н	Reflex™ Super T [®] -Stripper Wire Stripper	45-9615

Insulated Screwdrivers

Insulated Nutdrivers

Deer



Choff Lo

Description	Shaft Length	Cat. No.
#1 Phillips Screwdriver	3 in.	35-9310
#2 Phillips Screwdriver	4 in.	35-9311
#3 Phillips Screwdriver	6 in.	35-9312
1/8 in. Slotted Screwdriver	4 in.	35-9320
3/16 in. Slotted Screwdriver	5 in.	35-9321
7/32 in. Slotted Screwdriver	7 in.	35-9322
1/4 in. Slotted Screwdriver	6 in.	35-9323
5/16 in. Slotted Screwdriver	7 in.	35-9324
3/8 in. Slotted Screwdriver	8 in.	35-9325

Screwdriver Kit	Cat. No.
9-Piece Insulated Screwdriver Kit with hard case (Includes all nine screwdrivers listed above.)	35-9303

Insulated Knife



Description	Shall Length	Gal. NO.
3/16 in. Hex Nutdriver	5 in.	35-9330
1/4 in. Hex Nutdriver	5 in.	35-9331
5/16 in. Hex Nutdriver	5 in.	35-9332
3/8 in. Hex Nutdriver	5 in.	35-9333
7/16 in. Hex Nutdriver	5 in.	35-9334
1/2 in. Hex Nutdriver	5 in.	35-9335
9/16 in. Hex Nutdriver	5 in.	35-9336
Nutdriver Kit		Cat. No.
7-Piece Insulated Nutdriver Kit with hard case (Includes all seven Nutdrivers listed above.)		35-9304







- Test prods fit parallel and tandem slot receptacles
- Built-in resistors limit current flow to eliminate false indication
- For 9/16 in. to 1 in. fuses
- For use on fuses to 100A/250V and 60A/600V
- Test capacity from 100V to 600V AC/DC

Description	Cat. No.
Fuse Puller & Test Light	34-012

Safe-T-Grip® Fuse Pullers



- Maximum efficiency and convenience for removing or replacing cartridge-type fuses
- Three sizes handle fuses ranging from 0 to 600A
- Fully insulated, high-dielectric, glass-filled polypropylene construction
- Notched handles provide safe, no-slip grip
- Clearly marked amperage ranges
- Exceed MIL specifications

Description	Cat. No.
Small Puller for 250V, 9/32 in. to 1/2 in. dia. fuses; 5 in. long	34-001
Medium Puller for 0 to 100A/250V & 600V, 1/2 in. to 1 in. dia. fuses; 7-1/2 in. long	34-002
Large Puller for 31 to 600A/250V & 31 to 400A/600V, 3/4 in. to 2-1/2 in. dia. fuses; 11-3/4 in. long	34-003

Fuse Pullers



- Molded of tough, high-impact nylon for greater strength
- No-slip gripping surface and protective finger stops for added safety

Description	Cat. No.
Small Puller for 0 to 30A/250V, 1/4 in. to 1/2 in. dia. fuses; 5 in. long	34-015
Large Puller for 0 to 100A/250V & 0 to 60A/600V, 9/16 in. to 1 in. dia. fuses; 7-1/4 in. long	34-016

1000V Insulated Screw-Holding Screwdriver

- Split blade wedges into screw slot when collar is extended
- Holds screw in place when installing in hard to reach areas
- Easy to start screw when wearing gloves

Description	Cat. No.
1000V Insulated Screw Holding Screwdriver, 3/16 x 6 in. slotted Tip	35-9406





Cutting & Holemaking Tools

Maat Provide Planter / Drywal

or (152 mm) - 18 TPI Internet (152 mm) - 18 TPI Internet (152 mm) - 18 TPI Internet (152 mm) - 18 TPI

IDEAL cutting tools offer a powerful line-up that includes...

- New T.K.O. Carbide-Tipped Hole Cutters provide extreme productivity gains over traditional knockouts, even through stainless steel!
- A new line of Bul-Z-Eye[™] Self Feed Wood Boring Bits with twin cutting edges and superior construction that cuts smoother and faster holes than the competition
- Superior step drill bits that deliver! Dual fluted, titanium nitride coated bits with the NEW split-point self starting feature, deliver faster cuts, improved performance and longer tool life than conventional bits.
- Bi-metal reciprocating blades for the toughest applications. Engineered bi-metal blades last up to ten times longer than standard carbon steel blades.
- A broad line of flexible drill bits and specialty wood bits that deliver superior performance at any job site.
- An expanded range of hacksaws and allpurpose hand saws and blades.
Step Drill Bits











35-517

Improved Split-Point design for 3x faster starts

cooler operation.

Protective titanium nitrite coating

Double-fluted design

Radius-blended, multi-diameter steps

Trust IDEAL step drill bits for precise, repetitive drilling through the toughest materials including brass, carbon steel, cast iron, stainless steel, and more. These tough and reliable tools are constructed with a rugged titanium nitrite exterior coating. Each step is gradually blended to ease stepping through hole sizes; reducing the need to keep changing drill bits, which speeds up the fabrication process. Improved Split-Point tip design eliminates the need for a starter hole or punch and delivers three times faster starts, saving valuable time. The double-fluted design provides balanced cuts and

Drill Diameter Sizes (Inches)	No. of Hole Sizes	Step Increments (Inches)	Step Thickness (Inches)	Shank Dia. (Inches)	Cat. No.
1/8 to 1/2	13	1/32	1/8	1/4	35-511
1/4 to 3/4	9	1/16	1/8	3/8	35-512
1/4 to 7/8	11	1/16	1/16	3/8	35-513
1/2 to 1	8	1/16	1/8	3/8	35-514*
1/4 to 1-1/8	16	1/16	1/16	3/8	35-515
3/16 to 1/2	6	1/16	3/8	1/4	35-516
1/4 to 1-3/8	10	1/32	1/16 to 1/4	3/8	35-517

All shanks are 1 in. length.

*Requires pilot holes.

Electrician's Step Bit Kit Durable blow-molded case

- securely holds and protects bits
- Kit includes four step bits (35-511, 35-513, 35-515 and 35-517)
- Kit provides a solution for every electrical hole size between 1/8 in. and 1-3/8 in.

Description	Cat. No.
Electrician's Step Bit Kit	35-520



Carbide Tipped Hole Cutters

Introducing the new TKO[™] Carbide Tipped Hole Cutters from IDEAL INDUSTRIES, INC. TKO cutters offer the most efficient and clean cutter replacement for traditional knockouts, by



With SmoothStart" Pilot

making smooth holes in a fraction of the time at a fraction of the cost. Specifically designed to cut sheet metal, TKO cutters will even cut stainless steel with fine grained, carbide tips. The innovative design includes the exclusive SmoothStart[™] replaceable pilot drill, which guides the cutter to the surface, avoiding cutter damage and providing smoother holes. An integral overdrill flange prevents cutter penetration beyond the sheet metal. When it comes to quality, performance and durability, IDEAL is the professional's choice for carbide tipped hole cutters.

Carbide-Tipped Hole Cutters

Hole Size (Inches)	Conduit & Pipe Size (Inches)	Cat. No.
3/4	—	36-300
7/8	1/2	36-301
1	—	36-302
1-1/8	3/4	36-303
1-1/4	—	36-304
1-3/8	1	36-305
1-7/16	—	36-306
1-1/2	—	36-307
1-3/4	1-1/4	36-308
2	1-1/2	36-309
2-1/2		36-310





IDEAL TKO[™]

Competitor

IDEAL provides smoother, more precise hole than competitors (holes cut with 1-1/8 in. cutters)



Available in a full range of sizes from 1 in. to 2-1/2 in.

-
Cat. No.
36-312

Description	Cat. No.
4-Piece Carbide Hole Cutter Kit — Includes SmoothStart™ Replacement Tip, 7/8 in., 1-1/8 in., 1-3/8 in.	36-311

Integrated overdrill flange prevents penetration beyond the sheet metal.

www.idealindustries.com



Carbide Tipped Hole Cutters

Carbide tips cut over 200 holes through stainless steel, and outperform HSS cutters and bi-metal hole saws in sheet steel

Integral arbor provides smoother, more acurate holes than hole saws or two-piece carbidetipped cutters

Integraded overdrill flange prevents penetration beyond the sheet metal

Ejection spring effortlessly ejects slug

Exclusive SmoothStart™ pilot drill guides cutter

See how IDEAL TKO can save time...

Total time using the IDEAL **TKO**TM **30 Seconds**



Chuck Cutter



Total time using the competitors' knockout tool More than 6 Minutes

















IRONMAN[®] Bi-metal hole saws from IDEAL INDUSTRIES, INC, with re-engineered bi-metal construction, a thick "flex-free" backing plate, and variable sized teeth, IDEAL IRONMAN[®] hole saws will rival the cutting speed and longevity of any in the industry. The bi-metal construction cuts metal, wood and plastics including: tool and stainless steel, nail embedded wood, plywood, and pipe. An extensive list of 51 sizes, effective accessories, and kits are available to meet all your cutting needs. When it comes to quality, performance and durability, IDEAL is the professional's choice for hole saws.

New improved solid plate design resists flexing of the new hole saw for clean true holes and added durability Bi-metal construction combines hardened and durable tool steel teeth welded to fatigue resistant body for long and consistent cutting life Variable sized teeth clear chips away from the work quickly for faster cuts and reduced vibration 1-5/8 in. cutting depth cuts through 2' x 4's on the first cut Threads fit all standard arbors **Hole Saws**

Thicker, FLEX FREE backing plate for clean true holes and longer tool life



- Improved bi-metal construction for long life and durability
- Variable pitch tooth geometry for fast cutting and reduced vibration
- Cuts all types of machinable metal including stainless steel, wood, nail embedded wood, plastic and fiberboard

	Dine Ten	Dine Entrence	
Saw Diameter	Pipe Tap Size*	Pipe Entrance Size*	
(Inches)	(Inches)	(Inches)	Cat. No.
Use Arbor No. 35-391, 35-392 o	or 35-393		
9/16	_	—	35-340
5⁄8 11⁄16	_	_	35-341 35-342
3/4	1/2	3⁄8	35-343
13⁄16	_	_	35-344
7/8	3⁄4	1/2	35-345
15⁄16	_	—	35-346 35-347
1 1-1⁄16	_	_	35-347
1-1/8	1	3⁄4	35-349
1-3⁄16	_	_	35-350
Use Arbor No. 35-394,35-536 or 3	35-537		
1-1/4	_	_	35-351
1-5⁄16	_	_	35-352
1-3/8	_	1	35-353
1-7/16	—	—	35-354
1-1/2	1-1/4	_	35-355
1-9⁄16	_	_	35-356
1-5⁄8	_	_	35-357
1-11/19	_	_	35-358
1-3⁄4	1-1/2	1-1/4	35-359
1-13/16	_	_	35-360
1-7/8	_	_	35-361
2	_	1-1/2	35-362
2-1/16	_	_	35-363
2-1/8	_	_	35-364
2-1/4	2	_	35-365
2-5⁄16	_	_	35-366
2-3⁄8	_	_	35-367
2-1/2	_	2	35-368
2-9⁄16	_	_	35-369
2-5⁄8	2-1/2	_	35-370
2-3⁄4	_	_	35-371
2-7/8	_	_	35-372
Use Arbor No. 35-394, 35-536, 3	5-537 or 35-53		05 070
3	_	2-1/2	35-373
3-1/8	_	_	35-374
3-1/4	3	—	35-375
3-3/8	_	—	35-376
3-1/2	_	_	35-377
3-5/8	-	3	35-378
3-3/4	3-1/2		35-379
3-7/8	_	—	35-380
4	_	-	35-381
4-1/8	-	3-1/2	35-382
4-1/4	4	_	35-383
4-3/8	_	-	35-384
4-1/2	-	4	35-385
4-3⁄4	4-1/2	_	35-386
5	_	_	35-387
5-1/2	_	—	35-388
5-3⁄4	_	_	35-389
6	-	—	35-390

*All pipe sizes listed in the Pipe Tap Size and Pipe Entrance Size columns are standard industry sizes. All pipes are sized by the nominal inside diameter.

Hole Saw Arbors 35-301 35-302 35-303 35-394 35-536 35-537 35-538

Durable steel construction means years of long-lasting performance. Set-screw in body allows easy replacement of the pilot drill. Save valuable time through this versatile design. Instantly change hole saws without tools and without having to remove the arbor from the chuck.

Shank Size	Thread Size	Chuck Size	Fits Hole Saw Sizes	Cat. No.
1/4 in. Round	1/2-20 in.	1/4 in.	9/16 - 1-3/16 in.	35-391
3/8 in. Hex	1/2-20 in.	3/8 in.	9/16 - 1-3/16 in.	35-392
7/16 in. Hex	1/2-20 in.	1/2 in.	9/16 - 1-3/16 in.	35-393
7/16 in. Hex	5/8-18 in.	1/2 in.	1-1/4 - 6 in.	35-394
7/16 in. Hex	5/8-18 in.	1/2 in.	1-1/4 - 6 in.	35-536
3/8 in. Hex	5/8-18 in.	3/8 in.	1-1/4 - 6 in.	35-537
7/16 in. Hex	5/8-18 in.	1/2 in.	2 - 6 in.	35-538

Replacement Pilot Drills for Hole Saw Arbors

Split point pilot drills start on contact for faster penetration and less walking.

Description	Cat. No.
4-1/2 in. x 1/4 in Fits 35-391, 35-393, 35-394 & 35-538 arbors	35-397
3-1/4 in. x 1/4 in Fits 35-392, 35-536 & 35-537 arbors	35-398

Arbor Extension

For boring jobs that require a longer reach, arbor extensions add up to 18 in. length and can be easily connected to IDEAL hole saw arbors.

Description	Cat. No.
Extension for 7/16 in. Arbors, 12 in. long	35-396

Adjustable Can Light Hole Saws

- Cuts drywall and ceiling tile
- Self-sharpening carbide coated cutting blades
- Includes two dust shields to minimize clean up



Description	Cat. No.
Adjustable Can Light Hole Saw – 10 sizes from 2-1/2 in. to 7 in.	35-598
Adjustable Can Light Hole Saw – 13 sizes from 6-1/4 in. to 10-3/8 in.	35-599

Hole Saw Kits

Electrician's Hole Saw Kit

- Reliable 8-piece kit in a durable plastic case
- Find electrical sizes for pipe and conduit through 2 in.

Kit 35-400 Includes:

Description	Cat. No.
Hole Saw sizes 7/8 in., 1-1/8 in., 1-3/8 in., 1-3/4 in., 2 in. & 2-1/2 in. Also includes arbor models 35-393 & 35-394	35-400

14-Piece Electrician's Hole Saw Kit

- Generous 14-piece kit offers a tremendous selection
- Vou'll find electrical sizes for pipe and conduit through 4 in.
- Sturdy plastic case survives extra wear and tear

35-397

Kit 35-401 Includes:

Description	Cat. No.
Hole Saw sizes 7/8 in., 1-1/8 in., 1-3/8 in., 1-3/4 in., 2 in., 2-1/2 in., 3 in., 3-5/8 in., 4-1/8 in., 4-1/2 in. Also includes arbor models 35-391, 35-393 & 35-394 and extension bar 35-396.	35-401

19-Piece Master Electrician's Hole Saw Kit

- For electrical, industrial and all-purpose maintenance needs
- 19-piece kit comes in sturdy durable plastic case
- Plumbing and electrical sizes for pipe and conduit through 4 in.

Kit 35-518 Includes:

Description	Cat. No.
Hole Saw sizes 3/4 in., 7/8 in., 1 in., 1-1/8 in., 1-3/8 in., 1-1/2 in., 1-3/4 in., 2 in., 2-1/4 in., 2-1/2 in., 3 in., 3-5/8 in., 4-1/8 in. & 4-1/2 in. Also includes arbor models 35-393, 35-394, pilot drill 35-397 (two pieces) and extension bar 35-396.	35-518





Reciprocating Blades

- Bi-metal blades last up to ten times longer than carbon steel blades
- Flexible spring-back provides long blade life
- Super-hard, high speed steel teeth for a sharp, long-lasting cutting edge
- Shatterproof for tough applications
- Fits all reciprocating saws using 1/2 in. universal shank



	L/W/TH (Inches)	TPI	Material	Blade Bock	Qty.	Application	Cat. No.
Metal Cutting							
The and t	6 x 3/4 x .035	14	Bi-metal	Straight	5	Pipe, structural steel, stainless steel: 3/32" - 1/4", Non-ferrous metal: 3/32" - 3/8"	36-059
and U(17), and Minder Hilling	6 x 3/4 x .035	14	Bi-metal	Straight	25	Pipe, structural steel, stainless steel: 3/32" - 1/4", Non-ferrous metal: 3/32" - 3/8"	36-059B
Plant rep; 11 P	4 x 3/4 x .035	18	Bi-metal	Straight	5	Structural steel, pipe, conduit, stainless steel: 1/16" - 3/16" thick, Non-ferrous metal: 1/16" - 5//16" thick	36-055
the second	6 x 3/4 x .035	18	Bi-metal	Straight	5	Structural steel, pipe, conduit, stainless steel: 1/16" - 3/16" thick, Non-ferrous metal: 1/16" - 5/16" thick	36-057
	6 x 3/4 x .035	18	Bi-metal	Straight	25	Structural steel, pipe conduit, stainless steel: 1/16" - 3/16" thick, Non-ferrous metal: 1/16" - 5/16" thick	36-057B
Contract Contrac	8 x 3/4 x .035	18	Bi-metal	Straight	5	Structural steel, pipe, conduit, stainless steel: 1/16" - 3/16" thick, Non-ferrous metal: 1/16" - 5/16" thick	36-060
Transport	6 x 3/4 x .035	24	Bi-metal	Straight	5	All metal less than 1/8" thick: Tubing conduit, trim	36-058
	6 x 3/4 x .035	24	Bi-metal	Straight	25	All metal less than 1/8" thick: Tubing conduit, trim	36-058B
Heavy-Duty Metal Cutting							
and the second states and the second states	6 x 3/4 x .050	18	Bi-metal	Straight	2	Heavy-duty blade for cutting structural steel, pipe, conduit, stainless steel: 1/16" to 3/16" thick	36-085
The second secon	8 x 3/4 x .050	10/14	Bi-metal	Straight	2	Heavy-duty blade for cutting structural steel, pipe, conduit, stainless steel: 1/8" to 1/2" thick	36-086
If the set of the	12 x 3/4 x .050	10/14	Bi-metal	Taper	5	Heavy-duty blade for cutting structural steel, pipe, conduit, stainless steel: 1/8" to 1/2" thick	36-087
Wood w/Nails							
• mill Were and the second second	6 x 3/4 x .050	6	Bi-metal	Taper	5	Fast cutting, roughing-in work, nail-embedded wood, remodeling	36-065
	6 x 3/4 x .050	6	Bi-metal	Taper	25	Fast cutting, roughing-in work, nail-embedded wood, remodeling	36-065B
The second secon	9 x 3/4 x .050	6	Bi-metal	Taper	5	Fast cutting, roughing-in work, nail-embedded wood, remodeling	36-066
· · · ·	12 x 3/4 x .050	6	Bi-metal	Taper	5	Fast cutting, roughing-in work, nail-embedded wood, remodeling	36-067
Demolition							
- The second sec	9 x 7/8 x .062	6	Bi-metal	Taper	2	Demolition work in nail-embedded wood, remodeling	36-095
Control of the second s	9 x 7/8 x .062	10	Bi-metal	Taper	2	Demolition work in wood, metal, pipe and fire and rescue	36-096
General Purpose							
The second secon	6 x 3/4 x .035	10	Bi-metal	Straight	5	Nail embedded wood, metal and non-ferrous metal composition materials & plastics 1/8" - 1/2"	36-075
Specialty Cutting							
FCREE and 1-00 The Standard Balance March Balance	8 x 3/4 x .050	Grit	Tung. Grit	Straight	2	Iron pipe, fiberglass, reinforced plastics, ceramic tile, stone, slate and brick.	36-090
	3 x 5/16 x .035	18	Bi-Metal	Scroll	5	Scroll cutting wood, cast aluminum and non-ferrous metals	36-054
Plaster/Drywall							
	6 x 3/4 x .050	6	Bi-metal	Taper	2	For plaster, drywall, plaster board & lath. Bi-directional cutting	36-088



1-800-435-0705 for Customer Service

Long-Life Metal Cutting Reciprocating Blades

- Engineered to be the longest lasting, metal cutting blades available
- Long-life blades perform up to three times as many cuts as similar metal cutting blades
- 8% cobalt cutting edge for extreme durability
- Shatterproof bi-metal design
- Longer life for greater value



Long-Life Blades	L/W/TH (Inches)	ТРІ	Material	Blade Bock	Qty.	Application	Cat. No.
· man Versen of the same to the second of the second secon	6 x 3/4 x .035	18	Bi-metal	Straight	5	Long-Life blade for cutting structural steel, pipe, con- duit, stainless steel, sheet metal: 1/16" - 3/16" thick	36-043
• man and a state of a state of the state of	8 x 3/4 x .035	18	Bi-metal	Straight	5	Long-Life blade for cutting structural steel, pipe, con- duit, stainless steel, sheet metal: 1/16" - 3/16" thick	36-044
and and a state of the state of	6 x 1 x .042	14	Bi-metal	Straight	5	Long-life blade for cutting rebar, barstock, angle iron and other heavy gauge metals: 1/8" and thicker	36-046
	12 x 1 x .050	14	Bi-metal	Straight	5	Long-life blade for cutting rebar, barstock, angle iron and other heavy gauge metals: 1/8" and thicker	36-048



10.0 **Cutting Speed** 9.0 Average Speed of Cuts 8.0 (In Seconds) 7.0 6.0 5.0 4.0 3.0 2.0 1.0 0.0 Miln (.0.4.2)

Progressive Tooth Reciprocating Blades

- Specially designed for all purpose cutting
- Cut multiple materials without changing blades
- Tough bi-metal and HCS construction for long life.

Long-Life Blades	L/W/TH (Inches)	Material	Blade Bock	Qty.	Application	Cat. No.
a man Ar Critica i and i Angenesia Rati	6 x 3/4 x .035	Progressive	Bi-metal	5	All metal, non-ferrous metal, sheet metal, pipe and other metal materials	36-056
The second secon	8 x 3/4 x .050	Progressive	Bi-metal	5	For wood, nail-embedded wood, non-ferrous metals, plastic and fiberglass	36-076

Portable Band Saw Blades

- Bi-metal construction
- Fit all standard portable band saw machines

L/W/TH (Inches)	TPI	Qty./Pack	Cat. No.
44-7/8 x 1/2 x .020	10	3	36-070
44-7/8 x 1/2 x .020	14	3	36-071
44-7/8 x 1/2 x .020	18	3	36-072
44-7/8 x 1/2 x .020	24	3	36-073

- For pipe, tubing and solids
- Cut any machinable metal, including conduit, angle iron, structurals, rebar and stainless steel tubing







Introducing the new premium line of BULZ-EYE[™] self-feed wood boring bits from IDEAL INDUSTRIES, INC. BULZ-EYE™ self-feed bits include a number of superior features and benefits that combine to deliver the most outstanding performance of any self-feed bit product available today. The new design features twin cutting edges and precision ground teeth with up to 50% wider cutting surface. These features deliver improved cutting speeds, better balance and control, and clean more accurate holes then the leading brand in the market. BULZ-EYE[™] self-feed bits are manufactured with the best materials and machinery available to ensure quality, performance and consistency. The bits are also black oxide coated, heat treated and hardened for added durability. When it comes to quality, performance and durability, IDEAL is the professional's choice for self-feed bits.

Description	Diameter	Entrance Size for Pipe & EMT	Cat. No.
1 in. Self-Feed Wood Boring Bit	1 in.	1⁄2 in.	36-250
1-1/8 in. Self-Feed Wood Boring Bit	1-1⁄8 in.	—	36-251
1-1/4 in. Self-Feed Wood Boring Bit	1-1⁄4 in.	3⁄4 in.	36-252
1-3⁄8 in. Self-Feed Wood Boring Bit	1-3⁄8 in.	1 in.	36-253
1-1/2 in. Self-Feed Wood Boring Bit	1-1⁄2 in.	—	36-254
1-3⁄4 in. Self-Feed Wood Boring Bit	1-3⁄4 in.	1-1⁄4 in.	36-255
2 in. Self-Feed Wood Boring Bit	2 in.	1-1⁄2 in.	36-256
2-1⁄8 in. Self-Feed Wood Boring Bit	2-1⁄8 in.		36-257
2-1/4 in. Self-Feed Wood Boring Bit	2-1⁄4 in.		36-258
2-9⁄16 in. Self-Feed Wood Boring Bit	2-9⁄16 in.	2 in.	36-259
3 in. Self-Feed Wood Boring Bit	3 in.	2-1⁄2 in.	36-260
3-5⁄8 in. Self-Feed Wood Boring Bit	3-5⁄8 in.	3 in.	36-261
4-5⁄8 in. Self-Feed Wood Boring Bit	4-5⁄8 in.	4 in.	36-262
5-1⁄2 in. Extension	Ext	_	36-273
18 in. Extension	Ext		36-819

All bits are 4-5/8 in. long and come with a 7/16 in. shank designed to easily accommodate all 1/2 in. drill chucks.





Cuts a smoother, more accurate hole with less splintering than competitive bits. This decreases resistance during pipe installation and improves on-the-job productivity.

Robust replaceable lead screw with burr-free threads



Quickly powers through wet and treated woods with no binding or jamming.



Replacement Lead Screws

- Keeps self-feed bits running fast and true
- Easily replaced with hex wrench providing extended drill life and optimum cost-per-hole value



Description	Cat. No.
3-pack small replacement lead screws, fits bit sizes 1 in 2-9/16 in.	36-271
3-pack large replacement lead screws, fits bit sizes 3 in 4-5/8 in.	36-270

Extension Bars

- Cuts into hard-to-reach areas
- Fits IDEAL Auger Bits

Description	Cat. No.
5-1/2 in. Extension Bar	36-273
18 in. Extension Bar	35-819

Sharpening File

- Keeps durable bits working like new
- High-grade sharpener hones dulled edges quickly and efficiently

Description	Cat. No.
Sharpening File	36-272

5-Piece Kit

Includes four different bit sizes, a 5-1/2 in. extension bar, and a convenient carrying case, giving you everything you need for drilling multiple hole sizes in any wood material.

Kit 36-265 Includes:

Description	Cat. No.
5-1/2 in. extension bar, 1-3/8 in., 1-1/2 in., 2-1/8 in., 2-9/16 in. bits	36-265
_	

6-Piece Kit

	(many
Includes five	
different bit sizes, a	S INK
5-1/2 in. extension bar,	SI.
and a convenient carrying	1
case, giving you everything you	
need for drilling multiple hole sizes in	
any wood material.	

Kit 36-266 Includes:

Description	Cat. No.
5-1/2 in. extension bar, 1 in., 1-1/4 in., 1-3/8 in., 2 in., 2-9/16 in. bits	36-266

9-Piece Kit

Includes eight different bit sizes, a 5-1/2 in. extension bar, and a convenient carrying case, giving you everything you need for drilling multiple hole sizes in any wood material.

Kit 36-269 Includes:

Description	Cat. No.
5-1/2 in. extension bar, 1 in., 1-1/8 in., 1-1/4 in., 1-3/8 in., 1-1/2 in., 1-3/4 in., 2-1/8 in., 2-9/16 in. bits	36-269

Lead screws can be easily replaced with the use of a hex wrench providing extended drilling life and optimum cost-per-hole value.



www.idealindustries.com



Nailbiter[™] Premium Ship Auger Bits

- Dual-Helix construction with twin cutting edges provides faster and smoother drilling action, even through nail-embedded timbers
- Full body, dual induction heat treatment ensures durability, minimizes warping and delivers long lasting performance
- Heavy-duty lead screw designed for quick gripping power, superior penetration and extra-long life
- Re-sharpenable for extended tool life

Power Ship Augers - Bit Length = 7-1/2", Twist = 5", Shank = 7/16" Description	Hole Diameter	Overall Length	Twist Length	Cat. No.
5/8 in. Power Ship Auger	5/8 in.	7-1/2 in.	5 in.	35-810
11/16 in. Power Ship Auger	11/16 in.	7-1/2 in.	5 in.	35-811
3/4 in. Power Ship Auger	3/4 in.	7-1/2 in.	5 in.	35-812
13/16 in. Power Ship Auger	13/16 in.	7-1/2 in.	5 in.	35-813
7/8 in. Power Ship Auger	7/8 in.	7-1/2 in.	5 in.	35-814
1 in. Power Ship Auger	1 in.	7-1/2 in.	5 in.	35-815
1-1/8 in. Power Ship Auger	1-1/8 in.	7-1/2 in.	5 in.	35-816
1-1/4 in. Power Ship Auger	1-1/4 in.	7-1/2 in.	5 in.	35-817
Power Ship Augers - Bit Length = 18", Twist = 15", Shank = 7/16" Description	Hole Diameter	Overall Length	Twist Length	Cat. No.
1/2 in. Power Ship Auger	1/2 in.	18 in.	15 in.	35-820
5/8 in. Power Ship Auger	5/8 in.	18 in.	15 in.	35-821
11/16 in. Power Ship Auger	11/16 in.	18 in.	15 in.	35-822
3/4 in. Power Ship Auger	3/4 in.	18 in.	15 in.	35-823
13/16 in. Power Ship Auger	13/16 in.	18 in.	15 in.	35-824
7/8 in. Power Ship Auger	7/8 in.	18 in.	15 in.	35-825
15/16 in. Power Ship Auger	15/16 in.	18 in.	15 in.	35-826
1 in. Power Ship Auger	1 in.	18 in.	15 in.	35-827
1-1/8 in. Power Ship Auger	1-1/8 in.	18 in.	15 in.	35-828
1-1/4 in. Power Ship Auger	1-1/4 in.	18 in.	15 in.	35-829

Mini[™] Utility Bit Augers

- Designed to fit between wall studs when used with common drills
- Eliminates the need for expensive right angle drills

Mini™ Augers - Bit Length = 4-3/4" Twist = 2-1/2", Shank = 7/16" Description	Hole Diameter	Overall Length	Twist Length	Cat. No.
5/8 Mini™ Auger	5/8 in.	4-3/4 in.	2-1/2 in.	35-862
3/4 Mini™ Auger	3/4 in.	4-3/4 in.	2-1/2 in.	35-864
7/8 Mini™ Auger	7/8 in.	4-3/4 in.	2-1/2 in.	35-866
1 Mini™ Auger	1 in.	4-3/4 in.	2-1/2 in.	35-868

RESI-MASTER[™] Heavy-Duty Ship Augers

- 62° cutting angle reinforces the cutting edge and provides greater durability
- Hardened lead screw and cutting edge provide increased wear resistance and extended life
- Secondary relief angle evacuates wood chips quickly and prevents auger from jamming
- Oversized cutting head makes hole larger than body of bit for easy ejection from work piece

Power Ship Augers - Bit Length = 7-1/2", Twist = 5", Shank = 7/16" Description	Hole Diameter	Overall Length	Twist Length	Cat. No.
5/8 in. RESI-MASTER™ Auger	5/8 in.	7-1/2 in.	5 in.	35-892
11/16 in. RESI-MASTER™ Auger	11/16 in.	7-1/2 in.	5 in.	35-730
3/4 in. RESI-MASTER™ Auger	3/4 in.	7-1/2 in.	5 in.	35-893
13/16 in. RESI-MASTER™ Auger	13/16 in.	7-1/2 in.	5 in.	35-892
7/8 in. RESI-MASTER™Auger	7/8 in.	7-1/2 in.	5 in.	35-896
15/16 in. RESI-MASTER™ Auger	15/16 in.	7-1/2 in.	5 in.	35-897
1 in. RESI-MASTER™ Auger	1 in.	7-1/2 in.	5 in.	35-898
1-1/8 in. RESI-MASTER™ Auger	1-1/8 in.	7-1/2 in.	5 in.	35-899
1-1/4 in. RESI-MASTER™ Auger	1-1/4 in.	7-1/2 in.	5 in.	35-732
Power Ship Augers - Bit Length = 18",				
Twist = 15", Shank = 7/16" Description	Hole Diameter	Overall Length	Twist Length	Cat. No.
Twist = 15", Shank = 7/16"				
Twist = 15", Shank = 7/16" Description	Diameter	Length	Length	No.
Twist = 15", Shank = 7/16" Description 1/2 in. RESI-MASTER™ Auger	Diameter 1/2 in.	Length 18 in.	Length 15 in.	No. 35-726
Twist = 15", Shank = 7/16" Description 1/2 in. RESI-MASTER™ Auger 5/8 in. RESI-MASTER™ Auger	Diameter 1/2 in. 5/8 in.	Length 18 in. 18 in.	Length 15 in. 15 in.	No. 35-726 35-971
Twist = 15", Shank = 7/16" Description 1/2 in. RESI-MASTER™ Auger 5/8 in. RESI-MASTER™ Auger 11/16 in. RESI-MASTER™ Auger	Diameter 1/2 in. 5/8 in. 11/16 in.	Length 18 in. 18 in. 18 in.	Length 15 in. 15 in. 15 in.	No. 35-726 35-971 35-727
Twist = 15", Shank = 7/16" Description 1/2 in. RESI-MASTER™ Auger 5/8 in. RESI-MASTER™ Auger 11/16 in. RESI-MASTER™ Auger 3/4 in. RESI-MASTER™ Auger	Diameter 1/2 in. 5/8 in. 11/16 in. 3/4 in.	Length 18 in. 18 in. 18 in. 18 in.	Length 15 in. 15 in. 15 in. 15 in.	No. 35-726 35-971 35-727 35-972
Twist = 15", Shank = 7/16" Description 1/2 in. RESI-MASTER™ Auger 5/8 in. RESI-MASTER™ Auger 11/16 in. RESI-MASTER™ Auger 3/4 in. RESI-MASTER™ Auger 13/16 in. RESI-MASTER™ Auger	Diameter 1/2 in. 5/8 in. 11/16 in. 3/4 in. 13/16 in.	Length 18 in. 18 in. 18 in. 18 in. 18 in.	Length 15 in. 15 in. 15 in. 15 in. 15 in.	No. 35-726 35-971 35-727 35-972 35-728
Twist = 15", Shank = 7/16" Description 1/2 in. RESI-MASTER™ Auger 5/8 in. RESI-MASTER™ Auger 11/16 in. RESI-MASTER™ Auger 3/4 in. RESI-MASTER™ Auger 13/16 in. RESI-MASTER™ Auger 7/8 in. RESI-MASTER™ Auger	Diameter 1/2 in. 5/8 in. 11/16 in. 3/4 in. 13/16 in. 7/8 in.	Length 18 in. 18 in. 18 in. 18 in. 18 in. 18 in.	Length 15 in. 15 in. 15 in. 15 in. 15 in. 15 in.	No. 35-726 35-971 35-727 35-972 35-728 35-976
Twist = 15", Shank = 7/16" Description 1/2 in. RESI-MASTER™ Auger 5/8 in. RESI-MASTER™ Auger 11/16 in. RESI-MASTER™ Auger 3/4 in. RESI-MASTER™ Auger 13/16 in. RESI-MASTER™ Auger 7/8 in. RESI-MASTER™ Auger 15/16 in. RESI-MASTER™ Auger 15/16 in. RESI-MASTER™ Auger	Diameter 1/2 in. 5/8 in. 11/16 in. 3/4 in. 13/16 in. 7/8 in. 15/16 in.	Length 18 in. 18 in. 18 in. 18 in. 18 in. 18 in. 18 in.	Length 15 in. 15 in. 15 in. 15 in. 15 in. 15 in. 15 in.	No. 35-726 35-971 35-727 35-972 35-728 35-976 35-977

Auger Bit Extensions

*Dual locking scews	
Auger Bit Extensions, 18 in. Six flats to fit drill chuck – Allen wrench included Description	Cat. No.
Auger Bit Extension – 5/16 in.	35-818
Auger Bit Extension – 7/16 in.	35-819



Flexible Drill Bits



Professional drill bits drill and fish wire in one easy step. Drill and pull wire through blind areas in ceilings, walls and floors. Shanks are made from premium heat-treated spring steel for maximum flexibility while practically eliminating any retained shank bend. A three-flat non-slip grip on the shank and fish holes in both the tip and shank insure trouble-free wire pulling in either direction. Our tip design provides superior tip/shank contact, increasing the strength and durability of the braze and preventing separation when striking nails or other obstructions. Multiple styles are available for a variety of applications.

Best for

WOOD



Screw Point Flexible Bits, Type B

- Fast and aggressive, self-starting bit
- Ultra-sharp ground threads provide increased pulling power through obstructions
- Designed for easy to tough wood drilling

Description	Shank	Cat. No.
3/8 in. x 24 in. Screw Point Flexible Bit	3/16	90-080
3/8 in. x 36 in. Screw Point Flexible Bit	3/16	90-081
3/8 in. x 54 in. Screw Point Flexible Bit	3/16	90-082
3/8 in. x 72 in. Screw Point Flexible Bit	3/16	90-083
1/2 in. x 36 in. Screw Point Flexible Bit	3/16	90-084
1/2 in. x 54 in. Screw Point Flexible Bit	3/16	90-085
1/2 in. x 72 in. Screw Point Flexible Bit	3/16	90-086
9/16 in. x 36 in. Screw Point Flexible Bit	3/16	90-087
9/16 in. x 54 in. Screw Point Flexible Bit	3/16	90-088
9/16 in. x 72 in. Screw Point Flexible Bit	3/16	90-089
3/4 in. x 36 in. Screw Point Flexible Bit	1/4	90-090
3/4 in. x 54 in. Screw Point Flexible Bit	1/4	90-091
3/4 in. x 72 in. Screw Point Flexible Bit	1/4	90-092

Flexible Bit Extensions

Three lengths available for 3/16 in. and 1/4 in. shaft diameters



Connect to chuck end of shaft to increase the length of the bit

Description	Shank	Cat. No.
3/16 in. x 36 in. Flexible Bit Extension	3/16	90-170
3/16 in. x 54 in. Flexible Bit Extension	3/16	90-171
1/4 in. x 36 in. Flexible Bit Extension	1/4	90-173
1/4 in. x 54 in. Flexible Bit Extension	1/4	90-174

Flexible Bit Placement Tool

- Use as a positioning guide for the flexible drill bits
- Aids in more accurate placement of bit tips within walls
- Increases directional control during drilling

Description	Cat. No.
Flexible Bit Placement Tool	90-176

Serrated Combination Flexible Bits, Type C

- Multi-purpose versatile bit for clean holes
- Designed for easy to medium wood drilling and light metal
- Pressure is needed for starting and pulling the bit through the wood

Description	Shank	Cat. No.
1/4 in. x 54 in. Serrated Combination Flexible Bit	3/16	90-063
3/8 in. x 54 in. Serrated Combination Flexible Bit	3/16	90-067
1/2 in. x 54 in. Serrated Combination Flexible Bit	3/16	90-070
9/16 in. x 54 in. Serrated Combination Flexible Bit	3/16	90-073

Masonry Flexible Bits, Type M

Masonry drill bit

Description

Designed for drilling in lightweight masonry materials

	-	
-0-5		est for SONRY
	Shank	Cat. No.

ht WOOD ght MET/

Becomption	Giranin	out. Ho.
3/8 in. x 54 in. Masonry Flexible Bit	3/16	90-124
1/2 in. x 72 in. Masonry Flexible Bit	1/4	90-128

Installer Bits

- Hole in fluted head
 - for pulling wires through walls, ceiling and floors
- Flutes designed for quick chip removal no clogging or binding
- Premium quality, extra-hard 52-100 carbon bearing steel

Description	Length	Cat. No.
Installer Bit – 1/4 in.	18 in.	35-870
Installer Bit – 3/8 in.	18 in.	35-871
Installer Bit – 1/2 in.	18 in.	35-872

Flexible Drill

1-800-435-0705 for Customer Service





Jab Saw Heavy-Duty Hacksaw Cushioned ergonomic Contraction of the second second grip for performance and comfort Rugged frame provides lightweight rigidity and Includes replaceable bi-metal wallboard exceptional control blade Stores up to nine extra blades Holds all reciprocating blades and hacksaw blades Blades can be adjusted to 55° angle for flush cutting and Ergonomic grip tensioned to 30,000 psi Includes 12 in. x 24T bi-metal blade Description Cat. No. Heavy-Duty Hacksaw 35-260 Cat. No. Description 35-275 Jab Saw Replacement blade 36-088

Folding Saw

- Light-weight, heavy-duty die cast construction
- Ergonomic rubber comfort grip
- Blade safely and conveniently folds down in handle
- Accepts all standard 6 in. recip blades

Description	Cat. No.
Folding Saw	35-274

Aviation Tin Snips

- Chrome-molybdenum steel forged blades for greater strength and durability
- Serrated edges provide a stable hold when cutting
- Labor-saving design for easier cutting
- Comfortable non-slip dual durometer grips

Description	Cat. No.
Straight Cut Aviation Tin Snips	35-001

Ergonomic Hacksaw

- Angled handle for easier cutting
- Blade can easily be adjusted for flush cutting
- Easy tensioning wing-nut keeps blades tight for straighter cuts
- Cushioned ergonomic grip for performance and comfort
- Includes 12 in. x 24T bi-metal blade

Description	Cat. No.
Ergonomic Hacksaw	35-261

Mini Hacksaw

- Heavy-duty die cast frame
- Non-slip rubber comfort grip
- Accepts all standard hacksaw blades

Description	Cat. No.
Mini Hacksaw	35-259

Hacksaw Blades

Bi-metal blades provide strength, flexibility and longer life

Description	Qty./Pack	Cat. No.
12 in. x 18T Blades	10	35-271
12 in. x 24T Blades	10	35-272
12 in. x 32T Blades	10	35-273
12 in. x 18T Blades	100	35-262
12 in. x 24T Blades	100	35-263
12 in. x 32T Blades	100	35-264

