


COMPRESSION CONNECTORS

C-Taps

CTH SERIES



FEATURES

- These taps ensure positive, all-around compression with low resistance and high pull-out values.
- Made of high conductivity copper, they satisfy the requirements of NEC250-81 and 250-91 for connecting to the grounding electrode system.
- Rated for 600V applications.



COPPER "C" TAPS

- Range-taking compression connectors made from high conductivity copper alloy.
- Ideal for making tap or parallel copper connections from 8 SOL to 4/0 STR conductors.
- Provides consistent reliability with heavy wall construction that prevents relaxation of the joint after installation. Installation time is reduced because of its "C" shape.



UL486A/B Listed.

* CLASS B OR C BUILDING
WIRE CU CABLE ONLY

TEMPERATURE RATING:

90 °C. Rated 600V.



Scan QR to view
Tool & Die Charts

CAT. NO.	WIRE SIZE		COLOR CODE	STD. CTN. QTY.
	MAIN	BRANCH		
CTH-111	1	1	Blue	25
	1/0	1/0-2		
	2/0	2/0-4		
	3/0	1/0-6		
CTH-112	4/0	1-8	Brown	25
	2/0	2/0-1		
	3/0	3/0-3		
	4/0	4/0-4		
CTH-113	250	1/0-8	Pink	12
	2/0	2/0-1		
	3/0	3/0-2		
	4/0	4/0-4		
CTH-114	250	3/0-6	Black	6
	300	2/0-8		
	4/0	4/0-2/0		
	250	250-1		
CTH-115	300	4/0-4	Yellow	6
	350	3/0-6		
	250	250		
	300	300-3/0		
CTH-116	350	350-1/0	White	3
	400	300-2		
	450	250-4		
	500	250-6		
CTH-117	350	350-4/0	-	3
	400	400-2/0		
	450	450-1		
	500	500-2		
CTH-117	750-500	4/0-6	-	3
	750	750-4/0		

CAT. NO.	CONDUCTOR RANGE		STRIP LENGTH	STD. CTN. QTY.
	RUN	TAP		
CTH-46	6 SOL - 4 STR	6 SOL - 6 STR	3/4	25
CTH-44	6 SOL - 4 STR	4 SOL - 4 STR	3/4	25
CTH-24	2 SOL - 2 STR	8 SOL - 4 STR	7/8	10
CTH-22	2 SOL - 2 STR	2 SOL - 2 STR	7/8	25
CTH-2020	1/0 STR - 2/0 STR	1/0 STR - 2/0 STR	11/16	3
CTH-4020	3/0 STR - 4/0 STR	1/0 STR - 2/0 STR	13/16	3
CTH-4040	3/0 STR - 4/0 STR	3/0 STR - 4/0 STR	13/16	3

All dimensional data is listed in inches.

FOR TOOL & DIE CRIMPING INFORMATION,
PLEASE SEE TABLE ON PAGE 145