

Туре

Date

### DESCRIPTION

Lampholder utilizes 12V MR16 lamps and provides a very white crisp light. Lampholders are available in Satin White (P) or Matte Black (MB) finishes. Lazer lampholders are compatible with all Halo Power-Trac systems (except 4-Circuit Trac). Ideal for accent and display lighting applications where high coloring rendering and precise beam control are required.

#### SPECIFICATION FEATURES

#### A...Electrical Quick Lock Adapter/Transformer

Polycarbonate casing. Attaches electrically and mechanically anywhere along track. Visual polarity line assures proper grounding. Two position conductor allows use in single circuit and either circuit of two circuit track. All solid-state components lower 120V line voltage to lamp operating voltage.

## B...Arm

Matching polycarbonate arm allows lampholder to rotate 338° and adjust vertically from 0° to 90°. Constant tension pivot design holds desired aiming angle.

# C...Body

Deep drawn steel lamp housing with vents in rear keep socket temperatures within design limits.

# D...Baffle

Catalog #

Comments

Prepared by

Project

Die cast aluminum black baffle with lamp retention spring pulls out for relamping.

# Listings

UL/CSA listed for use with Halo and Lazer-by-Halo track and track systems





12V MR16 **STEP CYLINDER** LAMPHOLDER

Lazer by Halo



# **ORDERING INFORMATION** SAMPLE NUMBER: LZR406P



L =3 7/8" [98mm] E =6 3/4 " [171mm]



P=Satin White MB=Satin Black

Finishes

ADV021813 9/04 TAB: Lazer Lampholders and Track Sheet 13

Note: Specifications and Dimensions subject to change without notice.

ENERGY DATA

Power Factor: >.90 Input Watts: <50

THD: <30%

Input Amps: .45 Max.

Visit our web site at www.cooperlighting.com

Customer First Center 1121 Highway 74 South Peachtree City, GA 30269 770.486.4800 FAX 770 486.4801 Cooper Lighting 5925 McLaughlin Rd. Mississauga, Ontario, Canada L5R 1B8 905.507.4000 FAX 905.568.7049