



Harsh Environment Safety Switch with Viewing Window

DH324NDKW

UPC:782114140727

Dimensions:

Height: 35.38 INLength: 11.63 INWidth: 15.5 IN

Weight:61 LB

Notes:For 2-pole applications; use outside poles of 3-pole switch. Can be field modified to meetNEMA 3R rainproof requirements when a factory provided drain hole is opened.

Warranties:

 Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

• Special Features: Upper viewing window

• Type: Single-Throw

• Amperage Rating: 200A

• Enclosure: NEMA 12

• Enclosure Material: Painted galvanized steel

• Fuse Class Provision: Class H fuses

• Fuse Configuration: Fusible with neutral

• Number Of Poles: Three-pole

• Number Of Wires: Four-wire

• Product Category: Heavy Duty, Fusible with

neutral

Voltage Rating: 240V

• Max Hp Rating: 15 at 240 Vac Std. 1 Ph, 25 at 240 Vac Std. 3 Ph, 15 at 240 Vac TD 1 Ph, 60

at 240 Vac TD 3 Ph, 40 at 250 Vdc



Supporting documents:

- Eatons Volume 2-Commercial Distribution
- Eaton Specification Sheet DH324NDKW

Certifications:

UL Listed

Product compliance: No Data

© 2016 Eaton. All rights reserved.