elastimold Product Specifications

Issue Date: 10/04/2012 Page: 1 of 2 PSS-K1502A1 File:

15/25kV

200A Deadbreak Feed-thru Insert

K1502A1



Features:

- 15/25kV, 200 Amp Deadbreak Rated
- Fits standard Elastimold® bushing well
- Peroxide-cured insulation and jacket
- Provision for ground wire connection
- Provides extra deadbreak tap for well type connection
- Rotatable for 360° mounting

K1502A1 Deadbreak Feed-thru Insert

Applications:

The ELASTIMOLD® K1502A1 feed-thru insert is a fully-shielded, fully submersible separable insulated connector designed for de-energized operation. The feed-thru insert fits a standard ANSI bushing well interface. The K1502A1 is suitable for use on 15/25kV class systems and may be used as the bushing interface for connecting shielded cable to the following:

Sub-surface/Pad mount transformers Generators Regulators Reclosers Switchgear

Designed for use as an apparatus bushing interface, the K1502A1 should be installed in an Elastimold® universal bushing well and mated with an appropriate Elastimold® product. The K1502A1 is designed to mate with the following Elastimold® products including:

156LR Elbow

K150DR K151SR

Ratings:

Meets ANSI/IEEE Standard 386, Latest Revision

For 15kV Voltage Class:

8.3kV Max Phase-to-Ground - Operating Voltage

14.4kV Max Phase-to-Phase

95kV BIL - Impulse Withstand (1.2 x 50

microsecond wave)

34kV AC - One minute withstand

53kV DC - 15 minutes withstand

11kV AC - Corona Extinction @ 3pC sensitivity

200 Amp - Continuous

10kA Sym - 10 Cycles Momentary

For 25kV Voltage Class:

15.2kV Max Phase-to-Ground - Operating Voltage

26.3kV Max Phase-to-Phase

125kV BIL - Impulse Withstand (1.2 x 50

microsecond wave)

40kV AC - One minute withstand

78kV DC - 15 minutes withstand

19kV AC - Corona Extinction @ 3pC sensitivity

200 Amp - Continuous

10kA Sym - 10 Cycles Momentary




elastimold Product Specifications

Issue Date: 10/04/2012 Page: 2 of 2 PSS-K1502A1 File:

15/25kV

200A Deadbreak Feed-thru Insert

K1502A1



Ordering Instructions:

To order, specify number K1502A1 feed-thru insert.

Each kit contains the following:

1	Bushing Insert	K1502A1
2	Protective shipping cap	180-PPC
3	Lubricant	82-08
1	Installation Instruction	IS-0392
1	Mounting hardware	1502-10

Notes:

Bails are required but not included. Order separately.

