

Rittal – The System.

Faster – better – everywhere.

Hygienic Design Compact enclosure HD – HD 1308.600

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Hygienic Design Compact enclosure HD – HD 1308.600

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Version: Roof slope 30° towards the front

Material: Housing and door: Stainless steel 1.4301 (AISI 304)
Mounting plate: Carbon steel
HD lock inserts: Stainless steel 1.4404 (AISI 316L)
Seal: Silicone, compliant with FDA Guideline 21 CFR 177.2600

Surface finish: Housing and door: Brushed, grain 400, peak-to-valley height < 0.8 µm
Mounting plate: Zinc-plated
Seal: Blue, dyed (RAL 5010)

**Protection category
IP to IEC 60 529:** IP 66

**Protection category
IP to DIN 40 050-9:** IP 69K

**Protection category
NEMA:** NEMA 13
NEMA 4X

Supply includes: Housing of all-round solid construction
Door with fitted seal
Door catch on right, may be swapped to the left
Mounting plate

Base material: Stainless steel

Product features

Dimensions: Height (front): 650 mm (26 ")
Height (rear): 769 mm (30 ")
Width: 390 mm (15 ")

Depth: 210 mm (8.3 ")

Mounting plate: Height: 570 mm (22 ")
Width: 334 mm (13 ")

Number of cam locks: 2

Packaging unit: 1 pc(s).

Weight/packaging unit: 17.9 kg (39.5 lb.)

EAN: 4028177567634

Customs tariff number: 94032080

ETIM 6.0: EC000261

ETIM 5.0: EC000261

eCl@ss 8.0/8.1: 27180101

eCl@ss 7.0/7.1: 27180101

eCl@ss 6.0/6.1: 27180101

eCl@ss 5.1/5.1.4: 27180102

Product description (long): HD Compact enclosure, WHD: 390x650(H1)x769(H2)x210 mm, Stainless steel 1.4301, with mounting plate, with hinged door and silicone seal

Approvals

Approvals: UL + C-UL

Certificates: DGUV
EAC

Declarations: Declaration of conformity