

747 Series Stopper Plugs

Flameproof

Cable Gland Accessories.

NEC/CEC:
Class I, Groups A, B, C, D
Class II, Groups E, F, G
Class III
Type 4X; Ex d II
IP68

ATEX/IECEX:
II 2 GD Ex d IIC and Ex e II
Zone 1, Zone 2, Zone 21 and Zone 22 - Gas
Groups IIA, IIB, IIC
IM 2 Ex d I and Ex e I
IP66/68

Applications

- Stopper plug is designed for use from the outside of the enclosure to permanently or temporarily close any unused entries.
- Idea for use on flameproof electrical equipment in hazardous areas.
- In general, care should be taken to ensure that a suitable entry thread sealing washer is also selected and installed, where applicable, to ensure that an effective seal is made at the entry, thereby maintaining the integrity of the enclosure or equipment I.P. rating.

Features

- Catering to both Industrial and Hazardous Area applications the range covers a number of different metallic and non-metallic (e.g. Nylon) forms.
- Compensating Displacement Seal (CDS) system allows for use with Restricted Breathing equipment.
- Available with both external (Type A) or internal (Type B) Allen Key design.
- Internal Allen Key design is considered tamper proof. Once the equipment has been de-energized and the terminal chamber cover removed it can be removed from the inside.

Standard Materials

- Brass fully nickel plated

Options

- Copper-free aluminum: replace suffix -5 with 1
- 316L stainless steel: replace suffix -5 with 4
- Nylon: replace suffix -5 with 2

NEC/CEC Certifications and Compliances

- UL Standard: 886 (1203), E60079-0, E60079-1, E60079-7



- CSA Standard: C22.2 No. 30, CAN/CSA E60079-0, CAN/CSA E60079-1, CAN/CSA E60079-7
- cCSAus Certified: 113642

ATEX/IECEX Certifications and Compliances







- Certification Type 747
 - Gas: Zones 1
 - Type of Protection: Ex d IIC Gb (except Nylon), Ex e IIC Gb
 - Dust: Zone 20
 - Type of Protection: Ex ta IIC Da
- Conforming to ATEX 94/9/CE: II 2G 1D
- Operating Temperature: -60 °C to +200 °C (-76 °F to +392 °F) (Metallic) and -20 °C to +60 °C (-4 °F to +140 °F) (Nylon)
- CE Declaration of Conformity: DC07001
- ATEX Certificate: Sira 13ATEX1265X
- IECEx Certificate: IECEx SIR 13.0094X
- Other Certifications: UL, cCSAus
- Marine Approval: LLOYDS, DNV, ABS
- Index of Protection according EN/IEC 60529: IP66

INMETRO Certification

- INMETRO Certificate: TÜV 12.1333X

EURASEC Certification

- TC RU C-GB.Г505.B.00138

	A/F Socket in mm	Male Thread Size	Thread Length mm (in)	Nickel Plated Brass Catalog Number
 <p>Ex 'd' Recessed Stopper Plug Type 'A'</p>	8	M16	10.0 (0.394)	747DAM15
		M20	10.0 (0.394)	747DAM25
 <p>Ex 'd' Recessed Stopper Plug Type 'B'</p>	10	M25	10.0 (0.394)	747DAM35
		M32	10.0 (0.394)	747DAM45
		M40	10.0 (0.394)	747DAM55
		M50	10.0 (0.394)	747DAM65
		M63	10.0 (0.394)	747DAM75
 <p>Ex 'd' Recessed Stopper Plug Type 'B'</p>	10	M75	10.0 (0.394)	747DAM85
		M90	10.0 (0.394)	747DAM95
		1/2 NPT	10.0 (0.394)	747DAT15
 <p>Ex 'd' Recessed Stopper Plug Type 'B'</p>	10	3/4 NPT	10.0 (0.394)	747DAT25
		1 NPT	10.0 (0.394)	747DAT35
 <p>Ex 'd' Recessed Stopper Plug Type 'B'</p>	14	1-1/4 NPT	10.0 (0.394)	747DAT45
		1-1/2 NPT	10.0 (0.394)	747DAT55
		2 NPT	10.0 (0.394)	747DAT65
 <p>Ex 'd' Recessed Stopper Plug Type 'B'</p>	14	2-1/2 NPT	10.0 (0.394)	747DAT75
		3 NPT	10.0 (0.394)	747DAT85