


**RIGID TO EMT COMBINATION COUPLINGS - STEEL**Rigid-EMT Couplings, Set Screw Steel  
N/A**B31**

Catalog #: 1434

**APPLICATIONS**

For use when coupling rigid/IMC conduit to EMT conduit

Use RACO Cat. Nos. 1352 to 1354 when coupling threaded rigid/IMC conduit to EMT. Use RACO Cat. Nos. 1432 to 1434 when coupling unthreaded rigid/IMC conduit to EMT

**PRODUCT FEATURES**

All steel construction insures mechanical protection

All components are zinc electro plated for corrosion protection

UPC bar code fittings are individually polybagged with a preprinted UPC-A bar code, and packaged in pre-scored tear top cartons for an attractive presentation

N/A

**UL LISTED**

Standard 514B (1432 - 1434 only), UL File E195969

**GENERAL PRODUCT INFORMATION**

Trade Size: 1 in.

**DRAWING DIMENSIONS**

Dimension A: 3-1/16 in.

Dimension B: 1-21/64 in.

Dimension C: 1-11/64 in.

Thread Spec. D: 1/4-28 x 3/8 in. Pan Head

**PACKAGING**

Package Type: Carton

Ship Carton Qty.: 25

Product UPC-A Labeled: No

Weight (Lbs. Per/C): 35.90

Ship Carton Length (in.): 9.19

Ship Carton Width (in.): 5.50

Ship Carton Height (in.): 6.56

Ctn Weight (Lbs.): 8.98

UPC Number: 050169014349

I2of5: 50050169014344