

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

NOTES:

1. IDENTIFICATION: VERTICAL, (24) C-13
208V / 30A / SINGLE-PHASE POU

<u>PART NO.</u>	<u>COLOR</u>
VB0B1L4BT24M1	BLACK

2. ACCESSORY COMPONENTS:
 (4) 10-32 x 1/2" MOUNTING SCREWS
 (4) 12-24 x 1/2" MOUNTING SCREWS
 (2) #10-32 LOCKING COLLAR SCREWS
 (2) L-BRACKETS

3. DIMENSIONS IN PARENTHESES ARE METRIC (mm).

4. UL[®] & c-UL[®] LISTED 1950.

5. RoHS COMPLIANT.

6. VISIT OUR ON-LINE CATALOG AT WWW.PANDUIT.COM FOR A CURRENT LIST OF PRODUCTS APPLICABLE FOR USE WITH THIS PART.

7. MAXIMUM AVAILABLE POWER = 5 KW

PANDUIT P/N	WEIGHT
VB0B1L4BT24M11	13 lb (5.9 kg)


64.75 (1644.7)
TOOLLESS MOUNTING BUTTON LOCATION

CIRCUIT BREAKER
(15A THERMAL)
4 PLACES


1.72 (43.7)

1.61 (40.9)

10 FOOT INLET POWER CORD



PLUG
30 AMP, 250V, SINGLE-PHASE
TWIST LOCK
NEMA L6-30P



TWENTY-FOUR (24)
RECEPTACLES
15 AMP, 250V
STRAIGHT BLADE
IEC 60320/C13

00A	2-24-11	MAV	KRKE	RELEASED TO PRODUCTION	09V098CZ				
REV	DATE	BY	CHK	DESCRIPTION	ECN - R	CUST	SUP	OTH	

MODEL FILENAME		09V098CZ/00.PRT	
CAD FILENAME/LAYERS		09V098CZ_DC/00A.PRT	
PANDUIT CORP TINLEY PARK, ILLINOIS			
VERTICAL, (24) C-13 POWER OUTLET UNIT (VB0B1L4BT24M1) CUSTOMER DRAWING			
UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: INCHES [METRIC - MILLIMETER] ANGLE X.X +/- 0.03 X. +/- 0.8 X.XX +/- 0.015 X.X +/- 0.4 +/- 1° X.XXX +/- 0.005 X.XX +/- 0.13		UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THIRD ANGLE PROJECTION	
DRAWN BY MAV		SCALE NONE	
DATE 2-24-11		DRAWING NO. 09V098CZ	
CHK'D KRKE		DWG B	