Rittal - The System.

Faster – better – everywhere.

Air duct system for roof-mounted cooling units and roof-mounted air/water heat exchangers – SK 3286.870

Date: May 24, 2018



Air duct system for roof-mounted cooling units and roof-mounted air/water heat exchangers – SK 3286.870

created: 24.05.2018 build on www.rittal.com/us-en



Product description			_	_	
	Prod	uct	aah	crin	tion

Description: Cold air can be routed directly to specific areas of the enclosure using the air duct system.

This eliminates the risk of air short circuits due to self-ventilated installed devices. The dimensions of the shallow duct are W x H x D 229 x 1500 x 29 mm, and can be shortened to

the required length.

Material: Flame-resistant plastic to DIN 4102/B1

Color: RAL 7035

Supply includes: Flat duct

Compensating hose

Note: Do not direct cold air straight at active components.

When using the ducting system, the performance of the cooling unit may be reduced,

depending on the application in question.

For devices 3359..../3382...., the air duct adapter 3286.840 is additionally required.

Suitable for Model

No.:

3209....

3210....

3273....

3359....

3382....

3383....

3384....

3385....

Product features

Packaging unit:

1 pc(s).

© Rittal 2018

Weight/packaging unit:	4.15 kg (9.1 lb.)		
EAN:	4028177325449		
Customs tariff number:	39269097		
ETIM 6.0:	EC001292		
ETIM 5.0:	EC001292		
eCl@ss 8.0/8.1:	22410601		
eCl@ss 7.0/7.1:	27189269		
eCl@ss 6.0/6.1:	27189269		
eCl@ss 5.1/5.1.4:	27180792		
Product description (long):	SK Air duct system, for SK 3386/3387, WHD: 229 x 1500 x 29 mm		

© Rittal 2018 2