

Rittal – The System.

Faster – better – everywhere.

Modular climate control concept - Blue e cooling module **Total cooling output** **1.50 - 2.50 kW – SK** **3310.740**

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Modular climate control concept - Blue e cooling module Total cooling output 1.50 - 2.50 kW – SK 3310.740

created: 24.05.2018 build on www.rittal.com/us-en



Product description	
Description:	All cooling modules can be individually combined with each section door.
Material:	Carbon steel
Color:	RAL 7035
Protection category IP to IEC 60 529:	External circuit, IP 34 Internal circuit, IP 54
Supply includes:	Cooling module prepared for installation in section door Nano-coated condenser Integral electric condensate evaporation Wired ready for connection (plug-in terminal strip)
Note:	A plinth with a height of 100 or 200 mm is required for efficient operation
Product features	
Total cooling output to DIN EN 14511:	L 35 L 35 at 50 Hz: 2.5 kW (8530 BTU) L 35 L 35 at 60 Hz: 2.5 kW (8530 BTU) L 35 L 50 at 50 Hz: 1.76 kW (6005 BTU) L 35 L 50 at 60 Hz: 1.8 kW (6141 BTU)
Air throughput (unimpeded air flow):	External circuit: 1100 m³/h (647.4 cfm) Internal circuit: 1100 m³/h (647.4 cfm)

Rated operating voltage:	400 V, 3~, 50 Hz 460 V, 3~, 60 Hz
Temperature control:	e-Comfort Controller (factory setting +35°C)
Temperature range:	Operation (environment): +10°C...+55°C Setting range: +20°C...+55°C
Refrigerant/cooling medium:	Refrigerant: R134a Quantity: 1175 g (41.4 oz) Global Warming Potential (GWP): 1430 CO ₂ equivalent (CO ₂ e): 1.68 t
Rated power Pel:	L 35 L 35 at 50 Hz: 1.13 kW L 35 L 35 at 60 Hz: 1.48 kW L 35 L 50 at 50 Hz: 1.4 kW L 35 L 50 at 60 Hz: 1.75 kW
Rated current (max.):	At 50 Hz: 3.5 A At 60 Hz: 3.7 A
Start-up current (max.):	At 50 Hz: 13 A At 60 Hz: 14 A
Pre-fuse:	Motor circuit-breaker: 6,3 A...10 A
Energy efficiency ratio (EER) 50 Hz L35 L35 to DIN EN 14511:	2.21
Packaging unit:	1 pc(s).
Weight/packaging unit:	72 kg Note: Incl. section door weight
EAN:	4028177559820
Customs tariff number:	84158200
ETIM 6.0:	EC002510
ETIM 5.0:	EC002510
eCl@ss 8.0/8.1:	27180702
eCl@ss 7.0/7.1:	27180702
eCl@ss 6.0/6.1:	27180702
eCl@ss 5.1/5.1.4:	27180702

**Product description
(long):**

SK modular climate control concept, Cooling module Blue e, 2.5/2.52 kW, 400-460 V, 3~, 50/60 Hz

Approvals

Approvals: UR + C-UR

Certificates: EAC

Declarations: Declaration of conformity
Declaration of conformity - F-gas regulation