

Rittal – The System.

Faster – better – everywhere.

Enclosure internal fan for TS – SK 3108.024

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Enclosure internal fan for TS – SK 3108.024

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Description: To prevent hot-spots and support the air routing of active enclosure climate control components. Adjustable in two axes. Mounted on the TS 8 frame section. Several fans can be cascaded using the quick-release terminal strip.

Supply includes: Complete unit with radial fan ready for connection
Snap-on pivot device
Fasteners

Product features

Air throughput (unimpeded air flow): 160 m³/h

Unimpeded air flow (without filter mats):

Unimpeded air flow (with filter mats):

Rated operating voltage: 24 V (DC)

Rated power P_{el} : with DC: 3.5 W

Rated current (max.): with DC: 0.15 A

Packaging unit: 1 pc(s).

Weight/packaging unit: 1 kg (2.2 lb.)

EAN: 4028177220508

Customs tariff number:	84145915
ETIM 6.0:	EC000320
ETIM 5.0:	EC000320
eCl@ss 8.0/8.1:	27180716
eCl@ss 7.0/7.1:	27180716
eCl@ss 6.0/6.1:	27180716
eCl@ss 5.1/5.1.4:	27180705
Product description (long):	SK enclosure internal fan, 3.5 W, 24 V (DC)
Approvals	
Approvals:	Approval overview
Certificates:	EAC
Declarations:	Declaration of conformity