


Ground Rod Clamps

UL® Listed for both copper-clad and galvanized ground rods.

Type JWR — Wide-Range Ground Rod Clamp

- UL® Listed for direct burial in earth/concrete
- Constructed from bronze alloy and high-performance stainless steel bolt
- Provides wide range of connection sizes
- More than 300 lbs. torque capacity



DB UL SP


CAT. NO.	NOMINAL ROD DIA.		WIRE RANGE			DIMENSIONS (IN.)				
	(IN.)	(MM)	MAX.	MIN.	MAX. (MM²)	MIN. (MM²)	A (MAX.) BOLT	B	C	D
JWR	3/8*	9.5	1/0 Str.	10 Sol.	53.4	5.2	1.535	1.050	.812	.652
	1/2	12.7	1/0 Str.	10 Sol.	53.4	5.2	1.535	1.050	.812	.652
	5/8	15.8	1/0 Str.	10 Sol.	53.4	5.2	1.535	1.050	.812	.652
	3/4	19.0	1/0 Str.	8 Sol.	53.4	8.3	1.535	1.050	.812	.652

* 3/8" rod not recognized/listed by UL.

Long bearing surface of clamp on ground wire secures ground connection.

Type JAB — Ground Rod Clamps

- Cast of high-strength corrosion-resistant copper alloy
- Both hex head bolts and socket set screws available
- UL® Listed for direct burial



DB UL SP

CAT. NO.		NOMINAL ROD DIA.		WIRE RANGE				DIMENSIONS (IN.)					
SOCKET SET SCREW	HEX HEAD BOLT	(IN.)	(MM)	MAX.	MIN.	MAX. (MM²)	MIN. (MM²)	A (MAX.) SOCKET SCREW	A (MAX.) HEX BOLT	SCREW THREAD SIZE UNC-2A	B	C	D
JAB12*	JAB12H	½	12.7	2 Str.	10 Sol.	33.6	5.2	1 ¹⁹ / ₃₂	2 ³ / ₃₂	¼-14	2 ⁷ / ₃₂	⅛	1 ⁹ / ₃₂
JAB58	JAB58H	⅝	15.8	1/0 Str.	8 Sol.	53.4	8.3	1 ²⁷ / ₃₂	2 ¹³ / ₆₄	⅞-14	2 ⁹ / ₃₂	1	1 ¹ / ₁₆
JAB34	JAB34H	¾	19.0	1/0 Str.	8 Sol.	53.4	8.3	2	2 ¹¹ / ₃₂	⅞-14	1 ¹¹ / ₁₆	1	5 ¹ / ₆₄
—	JAB34C	¾ + ⅝	15.8 to 19.0	4/0 Str.	8 Sol.	95.0	8.3	—	2 ¹¹ / ₃₂	⅞-14	1 ¹ / ₈	1 ¹ / ₃₂	1 ⁹ / ₁₆
JAB1	JAB1H	1	25.0	4/0 Str.	8 Sol.	107.1	8.3	2¼	3	⅞-14	1 ¹¹ / ₃₂	1 ¹ / ₁₆	1

* Not CSA listed


Add suffix P to Cat. No. for tin-plated clamp.

Ground Rod Clamps

A dependable ground connection offered at a substantial savings.

Type G — Budget-Line Ground Clamps

- Cast of high-strength corrosion-resistant copper alloy
- Furnished with hex head bolts
- Simplified, compact design makes lasting, trouble-free connection
- UL® Listed for direct burial



CAT. NO.	NOMINAL ROD DIA.		WIRE RANGE				DIMENSIONS (IN.)					
	(IN.)	(MM)	MAX.	MIN.	MAX. (MM²)	MIN. (MM²)	A (MAX.) BOLT	SCREW THREAD SIZE UNC-2A	B	C	D	E
G3*	3/8	9.5	4 Str.	10 Sol.	21.1	5.2	1 1/8	5/16-18	1 1/16	1/2	2 1/64	3/8
G4	1/2	12.7	2 Str.	10 Sol.	33.6	5.2	—	3/8-16	2 1/32	3/8	3 1/64	1/2
G5†	5/8	15.8	2 Str.	10 Sol.	33.6	5.2	—	3/8-16	2 9/32	3/8	4 3/64	1/2
G6	3/4	19.0	2 Str.	10 Sol.	33.6	5.2	—	3/8-16	1 1/16	3/8	1 3/16	1/2

* Not UL Listed.


† RUS Accepted.

Add suffix P to Cat. No. for tin-plated clamp.


Axial groove keeps wire and rod in perfect alignment.

Types GG and GGH — Heavy-Duty Ground Rod Clamps

- Cast of high-strength corrosion-resistant copper alloy
- Both hex head bolts and socket set screws available
- Floating pressure bar distributes pressure evenly over large area of ground wire



Type GG



Type GGH



CAT. NO.*		NOMINAL ROD DIA.		WIRE RANGE				DIMENSIONS (IN.)				
SOCKET SET SCREW	HEX HEAD BOLT	(IN.)	(MM)	MAX.	MIN.	MAX. (MM²)	MIN. (MM²)	A (MAX.) SOCKET SCREW	A (MAX.) HEX BOLT	SCREW THREAD SIZE UNC-2A	B	C
GG12	GG12H	1/2	12.7	2 Str.	8 Sol.	33.6	8.3	1 13/64	1 1/16	7/16-14	2 1/32	1 5/16
GG58	GG58H	5/8	15.8	2 Str.	8 Sol.	53.6	8.3	1 51/64	2 1/32	7/16-14	6 1/64	1 5/16
—	GG34H	3/4	19.0	4/0 Str.	8 Sol.	120.6	8.3	—	3	1/2-14	1 3/8	1 1/4

* Add suffix P to Cat. No. for tin-plated clamp.

GG34H has no pressure bar or axial groove.

Ground Rod Clamps

Drive-on design provides easy, tool-free installation, high-reliability compression-fit connection and room for one or two ground leads.

Type DGC — Drive-On Ground Clamps

- High-strength copper alloy provides increased tensile strength and long-term corrosion resistance for direct-burial applications
- UL® 486A and UL® 467 Listed
- RUS Listed



CAT. NO.	GROUND ROD SIZE	GROUND WIRE SIZE
DGC58-44‡	½ (.555-.565)	(1) or (2) #4 Sol.
DGC58-66‡	¾ (.555-.565)	(1) or (2) #6 Sol.
DGC58-46*	¾ (.555-.565)	(1) #4 Sol., (1) #6 Sol.

‡ RUS Listed

* Not UL® Listed



Cable Tray Grounding Connector

- Malleable iron construction
- For use on cable tray up to ⅜" thick



CAT. NO.	GROUND WIRE RANGE (AWG)	CARRIAGE BOLT SIZE
10102-TB	#8 Solid to #2 Stranded	⅜"-18
10103-TB	#4 Stranded to 4/0 Stranded	⅝"-16

